
pyDAL Documentation

Release 15.7

web2py-developers

October 07, 2015

1	Indices and tables	3
1.1	Subpackages	3
1.2	Submodules	31
1.3	pydal.base module	31
1.4	pydal.connection module	39
1.5	pydal.objects module	39
1.6	Module contents	47
	Python Module Index	49

Contents:

Indices and tables

- *genindex*
- *modindex*
- *search*

1.1 Subpackages

1.1.1 pydal.adapters package

Submodules

pydal.adapters.base module

class `pydal.adapters.base.AdapterMeta`

Bases: `type`

Metaclass to support manipulation of adapter classes.

At the moment is used to intercept *entity_quoting* argument passed to DAL.

class `pydal.adapters.base.BaseAdapter` (*db, uri, pool_size=0, folder=None, db_codec='UTF-8', credential_decoder=<function IDENTITY at 0x7f61150dc320>, driver_args={}, adapter_args={}, do_connect=True, after_connection=None*)

Bases: `pydal.connection.ConnectionPool`

ADD (*first, second*)

AGGREGATE (*first, what*)

ALLOW_NULL ()

AND (*first, second*)

AS (*first, second*)

BELONGS (*first, second*)

CASE (*query, t, f*)

CAST (*first, second*)

COALESCE (*first, second*)

COALESCE_ZERO (*first*)

COMMA (*first, second*)

CONCAT (**items*)

CONTAINS (*first, second, case_sensitive=True*)

COUNT (*first, distinct=None*)

DIV (*first, second*)

ENDSWITH (*first, second*)

EPOCH (*first*)

EQ (*first, second=None*)

EXTRACT (*first, what*)

FALSE = 'F'

FALSE_exp = '0'

GE (*first, second=None*)

GT (*first, second=None*)

ILIKE (*first, second, escape=None*)
Case insensitive like operator

INVERT (*first*)

JOIN ()

LE (*first, second=None*)

LEFT_JOIN ()

LENGTH (*first*)

LIKE (*first, second, escape=None*)
Case sensitive like operator

LOWER (*first*)

LT (*first, second=None*)

MOD (*first, second*)

MUL (*first, second*)

NE (*first, second=None*)

NOT (*first*)

NOT_NULL (*default, field_type*)

ON (*first, second*)

OR (*first, second*)

PRIMARY_KEY (*key*)

QUOTE_TEMPLATE = "%s"

RANDOM ()

RAW (*first*)

REGEXP (*first, second*)
 Regular expression operator

REPLACE (*first, tup*)

STARTSWITH (*first, second*)

SUB (*first, second*)

SUBSTRING (*field, parameters*)

TRUE = 'T'

TRUE_exp = '1'

T_SEP = ' '

UPPER (*first*)

adapt (*obj*)

alias (*table, alias*)
 Given a table object, makes a new table object with alias name.

build_parsemap ()

bulk_insert (*table, items*)

can_join ()

can_select_for_update = True

close_connection ()

commit ()

commit_on_alter_table = False

commit_prepared (*key*)

common_filter (*query, tablename*)

concat_add (*tablename*)

connection = None

connector (**args, **kwargs*)

constraint_name (*table, fieldname*)

count (*query, distinct=None*)

create_sequence_and_triggers (*query, table, **args*)

create_table (*table, migrate=True, fake_migrate=False, polymodel=None*)

dbpath = None

delete (*tablename, query*)

distributed_transaction_begin (*key*)

driver = None

driver_auto_json = []

driver_name = None

drivers = ()

drop (*table, mode=''*)

execute (**a, **b*)

execute_test_query ()

expand (*expression, field_type=None, colnames=False*)

expand_all (*fields, tablenames*)

file_close (*fileobj*)

file_delete (*filename*)

file_exists (*filename*)

file_open (*filename, mode='rb', lock=True*)

find_driver (*adapter_args, uri=None*)

folder = None

get_table (**queries*)

id_query (*table*)

insert (*table, fields*)

isOperationalError (*exception*)

isProgrammingError (*exception*)

is_numerical_type (*ftype*)

iterparse (*sql, fields, colnames, blob_decode=True, cacheable=False*)
Iterator to parse one row at a time. It doesn't support the old style virtual fields

itersselect (*query, fields, attributes*)

lastrowid (*table*)

like_escaper_default (*term*)

log (*message, table=None*)
Logs migrations
It will not log changes if logfile is not specified. Defaults to sql.log

log_execute (**a, **b*)

migrate_table (*table, sql_fields, sql_fields_old, sql_fields_aux, logfile, fake_migrate=False*)

parse (*rows, fields, colnames, blob_decode=True, cacheable=False*)

parse_blob (*value, field_type*)

parse_boolean (*value, field_type*)

parse_date (*value, field_type*)

parse_datetime (*value, field_type*)

parse_decimal (*value, field_type*)

parse_double (*value, field_type*)

parse_id (*value, field_type*)

parse_integer (*value, field_type*)

parse_json (*value, field_type*)

parse_list_integers (*value, field_type*)

```

parse_list_references (value, field_type)
parse_list_strings (value, field_type)
parse_reference (value, field_type)
parse_time (value, field_type)
parse_value (value, field_type, blob_decode=True)
prepare (key)
represent (obj, fieldtype)
represent_exceptions (obj, fieldtype)
rollback ()
rollback_prepared (key)
rowslice (rows, minimum=0, maximum=None)
    By default this function does nothing; overload when db does not do slicing.
save_dbt (table, sql_fields_current)
select (query, fields, attributes)
    Always returns a Rows object, possibly empty.
select_limitby (sql_s, sql_f, sql_t, sql_w, sql_o, limitby)
sequence_name (tablename)
smart_adapt (obj)
sqlsafe_field (fieldname)
sqlsafe_table (tablename, ot=None)
support_distributed_transaction = False
table_alias (tbl)
tables (*queries)
test_query = 'SELECT 1;'
trigger_name (tablename)
truncate (table, mode=' ')
types = {'reference': 'INTEGER REFERENCES %(foreign_key)s ON DELETE %(on_delete_action)s %(null)s %(unicod
update (tablename, query, fields)
uploads_in_blob = False
varquote (name)
class pydal.adapters.base.NoSQLAdapter (db, uri, pool_size=0, folder=None, db_codec='UTF-8', credential_decoder=<function IDENTITY at 0x7f61150dc320>, driver_args={}, adapter_args={}, do_connect=True, after_connection=None)
    Bases: pydal.adapters.base.BaseAdapter
ADD (first, second)
AGGREGATE (first, what)
AND (first, second)

```

AS (*first, second*)

DIV (*first, second*)

ENDSWITH (*first, second=None*)

EXTRACT (*first, what*)

ILIKE (*first, second*)

LEFT_JOIN ()

LENGTH (*first*)

LOWER (*first*)

MUL (*first, second*)

ON (*first, second*)

OR (*first, second*)

PRIMARY_KEY (*key*)

QUOTE_TEMPLATE = '%s'

RANDOM ()

STARTSWITH (*first, second=None*)

SUB (*first, second*)

SUBSTRING (*field, parameters*)

UPPER (*first*)

can_join ()

can_select_for_update = **False**

close_connection ()
remember: no transactions on many NoSQL

commit ()
remember: no transactions on many NoSQL

commit_prepared (*key*)

concat_add (*table*)

constraint_name (*table, fieldname*)

create_sequence_and_triggers (*query, table, **args*)

distributed_transaction_begin (*key*)

drop (*table, mode*)

execute (**a, **b*)

execute_test_query ()
NoSql DBs don't have a universal query language. Override this specific driver if need to test connection status. Throw exception on failure.

id_query (*table*)

lastrowid (*table*)

log_execute (**a, **b*)

```

migrate_table (*a, **b)
parse_list_integers (value, field_type)
parse_list_references (value, field_type)
parse_list_strings (value, field_type)
prepare (key)
represent (obj, fieldtype)
represent_exceptions (obj, fieldtype)
rollback ()
    remember: no transactions on many NoSQL
rollback_prepared (key)
rowslice (rows, minimum=0, maximum=None)

```

pydal.adapters.couchdb module

```

class pydal.adapters.couchdb.CouchDBAdapter (db, uri='couchdb://127.0.0.1:5984',
    pool_size=0, folder=None, db_codec='UTF-8',
    credential_decoder=<function IDENTITY at 0x7f61150dc320>, driver_args={},
    adapter_args={}, do_connect=True, after_connection=None)

```

Bases: `pydal.adapters.base.NoSQLAdapter`

AND (first, second)

COMMA (first, second)

EQ (first, second)

NE (first, second)

OR (first, second)

count (query, distinct=None)

create_table (table, migrate=True, fake_migrate=False, polymodel=None)

delete (tablename, query)

drivers = ('couchdb',)

expand (expression, field_type=None)

file_close (fileobj)

file_exists (filename)

file_open (filename, mode='rb', lock=True)

insert (table, fields)

represent (obj, fieldtype)

select (query, fields, attributes)

types = {'string': <type 'str'>, 'reference': <type 'long'>, 'text': <type 'str'>, 'id': <type 'long'>, 'float': <type 'float'>},

update (tablename, query, fields)

```
uploads_in_blob = True
```

pydal.adapters.cubrid module

```
class pydal.adapters.cubrid.CubridAdapter (db, uri, pool_size=0, folder=None,
                                           db_codec='UTF-8', credential_decoder=<function IDENTITY at
                                           0x7f61150dc320>, driver_args={},
                                           adapter_args={}, do_connect=True, after_connection=None)
```

Bases: `pydal.adapters.mysql.MySQLAdapter`

```
REGEX_URI = <_sre.SRE_Pattern object at 0x14b9e10>
```

```
after_connection ()
```

```
drivers = ('cubridb',)
```

pydal.adapters.db2 module

```
class pydal.adapters.db2.DB2Adapter (db, uri, pool_size=0, folder=None, db_codec='UTF-8',
                                      credential_decoder=<function IDENTITY at
                                      0x7f61150dc320>, driver_args={}, adapter_args={},
                                      do_connect=True, after_connection=None)
```

Bases: `pydal.adapters.base.BaseAdapter`

```
LEFT_JOIN ()
```

```
RANDOM ()
```

```
drivers = ('ibm_db_dbi', 'pyodbc')
```

```
execute (command, placeholders=None)
```

```
lastrowid (table)
```

```
represent_exceptions (obj, fieldtype)
```

```
rowslice (rows, minimum=0, maximum=None)
```

```
select_limitby (sql_s, sql_f, sql_t, sql_w, sql_o, limitby)
```

```
types = {'reference': 'INT, FOREIGN KEY (%(field_name)s) REFERENCES %(foreign_key)s ON DELETE %(on_del
```

pydal.adapters.firebird module

```
class pydal.adapters.firebird.FireBirdAdapter (db, uri, pool_size=0, folder=None,
                                                db_codec='UTF-8', credential_decoder=<function IDENTITY at
                                                0x7f61150dc320>, driver_args={},
                                                adapter_args={}, do_connect=True, after_connection=None)
```

Bases: `pydal.adapters.base.BaseAdapter`

```
CONTAINS (first, second, case_sensitive=False)
```

```
EPOCH (first)
```

```
LENGTH (first)
```

```
NOT_NULL (default, field_type)
```

```

RANDOM ()
REGEX_URI = <_sre.SRE_Pattern object at 0x158d8b0>
SUBSTRING (field, parameters)
commit_on_alter_table = True
create_sequence_and_triggers (query, table, **args)
drivers = ('kinterbasdb', 'firebirdsql', 'fdb', 'pyodbc')
lastrowid (table)
select_limitby (sql_s, sql_f, sql_t, sql_w, sql_o, limitby)
sequence_name (tablename)
support_distributed_transaction = True
trigger_name (tablename)
types = {'reference': 'INTEGER REFERENCES %(foreign_key)s ON DELETE %(on_delete_action)s', 'text': 'BLOB'}
class pydal.adapters.firebird.FireBirdEmbeddedAdapter (db, uri, pool_size=0,
                                                    folder=None,
                                                    db_codec='UTF-8', credential_decoder=<function IDENTITY at 0x7f61150dc320>,
                                                    driver_args={}, adapter_args={},
                                                    do_connect=True, after_connection=None)
Bases: pydal.adapters.firebird.FireBirdAdapter
REGEX_URI = <_sre.SRE_Pattern object at 0x1598790>
drivers = ('kinterbasdb', 'firebirdsql', 'fdb', 'pyodbc')

```

pydal.adapters.google_adapters module

Adapter for GAE

pydal.adapters.imap module

```

class pydal.adapters.imap.IMAPAdapter (db, uri, pool_size=0, folder=None, db_codec='UTF-8',
                                       credential_decoder=<function IDENTITY at 0x7f61150dc320>,
                                       driver_args={}, adapter_args={},
                                       do_connect=True, after_connection=None)
Bases: pydal.adapters.base.NoSQLAdapter

```

IMAP server adapter

This class is intended as an interface with email IMAP servers to perform simple queries in the web2py DAL query syntax, so email read, search and other related IMAP mail services (as those implemented by brands like Google(r), and Yahoo!(r) can be managed from web2py applications.

The code uses examples by Yuji Tomita on this post: <http://yuji.wordpress.com/2011/06/22/python-imaplib-imap-example-with-gmail/#comment-1137> and is based in docs for Python imaplib, python email and email IETF's (i.e. RFC2060 and RFC3501)

This adapter was tested with a small set of operations with Gmail(r). Other services requests could raise command syntax and response data issues.

It creates its table and field names “statically”, meaning that the developer should leave the table and field definitions to the DAL instance by calling the adapter’s .define_tables() method. The tables are defined with the IMAP server mailbox list information.

.define_tables() returns a dictionary mapping dal tablename to the server mailbox names with the following structure:

```
{<tablename>: str <server mailbox name>}
```

Here is a list of supported fields:

Field	Type	Description
uid	string	
answered	boolean	Flag
created	date	
content	list:string	A list of dict text or html parts
to	string	
cc	string	
bcc	string	
size	integer	the amount of octets of the message*
deleted	boolean	Flag
draft	boolean	Flag
flagged	boolean	Flag
sender	string	
recent	boolean	Flag
seen	boolean	Flag
subject	string	
mime	string	The mime header declaration
email	string	The complete RFC822 message (*)
attachments	list	Each non text part as dict
encoding	string	The main detected encoding

(*) At the application side it is measured as the length of the RFC822 message string

WARNING: As row id’s are mapped to email sequence numbers, make sure your imap client web2py app does not delete messages during select or update actions, to prevent updating or deleting different messages. Sequence numbers change whenever the mailbox is updated. To avoid this sequence numbers issues, it is recommended the use of uid fields in query references (although the update and delete in separate actions rule still applies).

```
# This is the code recommended to start imap support
# at the app's model:
```

```
imapdb = DAL("imap://user:password@server:port", pool_size=1) # port 993 for ssl
imapdb.define_tables()
```

Here is an (incomplete) list of possible imap commands:

```
# Count today's unseen messages
# smaller than 6000 octets from the
# inbox mailbox

q = imapdb.INBOX.seen == False
q &= imapdb.INBOX.created == datetime.date.today()
q &= imapdb.INBOX.size < 6000
unread = imapdb(q).count()
```



```

# Fetch last query messages
rows = imapdb(q).select()

# it is also possible to filter query select results with limitby and
# sequences of mailbox fields

set.select(<fields sequence>, limitby=(<int>, <int>))

# Mark last query messages as seen
messages = [row.uid for row in rows]
seen = imapdb(imapdb.INBOX.uid.belongs(messages)).update(seen=True)

# Delete messages in the imap database that have mails from mr. Gumby

deleted = 0
for mailbox in imapdb.tables
    deleted += imapdb(imapdb[mailbox].sender.contains("gumby")).delete()

# It is possible also to mark messages for deletion instead of ereasing them
# directly with set.update(deleted=True)

# This object give access
# to the adapter auto mailbox
# mapped names (which native
# mailbox has what table name)

imapdb.mailboxes <dict> # tablename, server native name pairs

# To retrieve a table native mailbox name use:
imapdb.<table>.mailbox

### New features v2.4.1:

# Declare mailboxes statically with tablename, name pairs
# This avoids the extra server names retrieval

imapdb.define_tables({"inbox": "INBOX"})

# Selects without content/attachments/email columns will only
# fetch header and flags

imapdb(q).select(imapdb.INBOX.sender, imapdb.INBOX.subject)

AND (first, second)

BELONGS (first, second)

CONTAINS (first, second, case_sensitive=False)

EQ (first, second)

GE (first, second)

GT (first, second)

LE (first, second)

LT (first, second)

NE (first, second=None)

```

NOT (*first*)

OR (*first, second*)

REGEX_URI = <_sre.SRE_Pattern object at 0x7f61150bc8c8>

convert_date (*date, add=None, imf=False*)

count (*query, distinct=None*)

create_table (**args, **kwargs*)

dbengine = 'imap'

define_tables (*mailbox_names=None*)

Auto create common IMAP files

This function creates fields definitions “statically” meaning that custom fields as in other adapters should not be supported and definitions handled on a service/mode basis (local syntax for Gmail(r), Ymail(r))

Returns a dictionary with tablename, server native mailbox name pairs.

delete (*tablename, query*)

drivers = ('imaplib',)

encode_text (*text, charset, errors='replace'*)

convert text for mail to unicode

get_charset (*message*)

get_last_message (*tablename*)

get_mailboxes ()

Query the mail database for mailbox names

get_query_mailbox (*query*)

get_uid_bounds (*tablename*)

static header_represent (*f, r*)

insert (*table, fields*)

is_flag (*flag*)

reconnect (*f=None*)

IMAP4 Pool connection method

imap connection lacks of self cursor command. A custom command should be provided as a replacement for connection pooling to prevent uncaught remote session closing

select (*query, fields, attributes*)

Searches and Fetches records and return web2py rows

types = {'boolean': <type 'bool'>, 'string': <type 'str'>, 'list:string': <type 'str'>, 'integer': <type 'int'>, 'date': <type 'date'>}

update (*tablename, query, fields*)

uri = None

MESSAGE is an identifier for sequence number

pydal.adapters.informix module

```
class pydal.adapters.informix.InformixAdapter(db, uri, pool_size=0, folder=None,
                                             db_codec='UTF-8', credential_decoder=<function IDENTITY at 0x7f61150dc320>, driver_args={}, adapter_args={}, do_connect=True, after_connection=None)
```

Bases: `pydal.adapters.base.BaseAdapter`

NOT_NULL (*default, field_type*)

RANDOM ()

REGEX_URI = <_sre.SRE_Pattern object at 0x7f611512ec30>

drivers = ('informixdb',)

execute (*command*)

lastrowid (*table*)

represent_exceptions (*obj, fieldtype*)

select_limitby (*sql_s, sql_f, sql_t, sql_w, sql_o, limitby*)

types = {'reference': 'INTEGER REFERENCES %(foreign_key)s ON DELETE %(on_delete_action)s', 'text': 'BLOB'}

```
class pydal.adapters.informix.InformixSEAdapter(db, uri, pool_size=0, folder=None,
                                                db_codec='UTF-8', credential_decoder=<function IDENTITY at 0x7f61150dc320>, driver_args={}, adapter_args={}, do_connect=True, after_connection=None)
```

Bases: `pydal.adapters.informix.InformixAdapter`

work in progress

rowslice (*rows, minimum=0, maximum=None*)

select_limitby (*sql_s, sql_f, sql_t, sql_w, sql_o, limitby*)

pydal.adapters.ingres module

```
class pydal.adapters.ingres.IngresAdapter(db, uri, pool_size=0, folder=None,
                                             db_codec='UTF-8', credential_decoder=<function IDENTITY at 0x7f61150dc320>, driver_args={}, adapter_args={}, do_connect=True, after_connection=None)
```

Bases: `pydal.adapters.base.BaseAdapter`

LEFT_JOIN ()

RANDOM ()

create_sequence_and_triggers (*query, table, **args*)

drivers = ('pyodbc',)

lastrowid (*table*)

select_limitby (*sql_s, sql_f, sql_t, sql_w, sql_o, limitby*)

```
types = {'reference': 'INT, FOREIGN KEY (%(field_name)s) REFERENCES %(foreign_key)s ON DELETE %(on_del

class pydal.adapters.ingres.IngresUnicodeAdapter(db, uri, pool_size=0, folder=None,
                                                db_codec='UTF-8', credential_decoder=<function IDENTITY
                                                at 0x7f61150dc320>, driver_args={},
                                                adapter_args={}, do_connect=True,
                                                after_connection=None)

Bases: pydal.adapters.ingres.IngresAdapter

drivers = ('pyodbc',)

types = {'reference': 'INTEGER4, FOREIGN KEY (%(field_name)s) REFERENCES %(foreign_key)s ON DELETE %
```

pydal.adapters.mongo module

```
class pydal.adapters.mongo.Binary
    Bases: object

class pydal.adapters.mongo.MongoBlob
    Bases: pydal.adapters.mongo.Binary

    MONGO_BLOB_BYTES = 0

    MONGO_BLOB_NON_UTF8_STR = 1

    static decode (value)

class pydal.adapters.mongo.MongoDBAdapter(db, uri='mongodb://127.0.0.1:5984/db',
                                           pool_size=0, folder=None, db_codec='UTF-
                                           8', credential_decoder=<function IDEN-
                                           TITY at 0x7f61150dc320>, driver_args={},
                                           adapter_args={}, do_connect=True, af-
                                           ter_connection=None)

Bases: pydal.adapters.base.NoSQLAdapter

ADD (first, *args, **kwargs)

AGGREGATE (first, *args, **kwargs)

AND (first, second)

AS (first, *args, **kwargs)

AS_MARK = '__#AS#__'

BELONGS (first, second)

CASE (query, true, false)

CMP_OPS_AGGREGATION_PIPELINE (op, first, second)

COMMA (first, second)

CONTAINS (first, second, case_sensitive=True)

COUNT (first, *args, **kwargs)

DIV (first, *args, **kwargs)

ENDSWITH (first, second)

EPOCH (first, *args, **kwargs)

EQ (first, second=None, *args, **kwargs)
```

EXPAND_CASE (*first, *args, **kwargs*)

EXTRACT (*first, *args, **kwargs*)

class Expanded (*adapter, crud, query, fields=(), tablename=None, groupby=None*)

Bases: object

Class to encapsulate a pydal expression and track the parse expansion and its results.

annotate_expression (*expression*)

get_collection (*safe=None*)

MongoDBAdapter.**GE** (**args, **kwargs*)

MongoDBAdapter.**GROUP_MARK** = ‘`__#GROUP#__`’

MongoDBAdapter.**GT** (**args, **kwargs*)

MongoDBAdapter.**ILIKE** (*first, second, escape=None*)

MongoDBAdapter.**INVERT** (*first*)

MongoDBAdapter.**LE** (**args, **kwargs*)

MongoDBAdapter.**LENGTH** (*first*)

<https://jira.mongodb.org/browse/SERVER-5319> <https://github.com/afchin/mongo/commit/f52105977e4d0ccb53bddd9c45>

MongoDBAdapter.**LIKE** (*first, second, case_sensitive=True, escape=None*)

MongoDBAdapter.**LOWER** (*first, *args, **kwargs*)

MongoDBAdapter.**LT** (**args, **kwargs*)

MongoDBAdapter.**MOD** (*first, *args, **kwargs*)

MongoDBAdapter.**MUL** (*first, *args, **kwargs*)

MongoDBAdapter.**NE** (*first, second=None, *args, **kwargs*)

MongoDBAdapter.**NOT** (*first*)

exception MongoDBAdapter.**NotOnNoSqlError** (*message=None*)

Bases: exceptions.NotImplementedError

MongoDBAdapter.**ON** (*first, second*)

MongoDBAdapter.**OR** (*first, second*)

MongoDBAdapter.**RANDOM** ()

ORDER BY RANDOM()

<https://github.com/mongodb/cookbook/blob/master/content/patterns/random-attribute.txt>

<https://jira.mongodb.org/browse/SERVER-533> <http://stackoverflow.com/questions/19412/how-to-request-a-random-row-in-sql>

MongoDBAdapter.**REGEXP** (*first, second, case_sensitive=True*)

MongoDB provides regular expression capabilities for pattern matching strings in queries. MongoDB uses Perl compatible regular expressions (i.e. ‘PCRE’) version 8.36 with UTF-8 support.

MongoDBAdapter.**REGEXP_MARK1** = ‘`__#REGEXP_1#__`’

MongoDBAdapter.**REGEXP_MARK2** = ‘`__#REGEXP_2#__`’

MongoDBAdapter.**REGEX_SELECT_AS_PARSER** = <_sre.SRE_Pattern object at 0x7f61150ca1b8>

MongoDBAdapter.**STARTSWITH** (*first, second*)

MongoDBAdapter.**SUB** (*first, *args, **kwargs*)

MongoDBAdapter.**SUBSTRING** (*first, *args, **kwargs*)
 MongoDBAdapter.**UPPER** (*first, *args, **kwargs*)
 MongoDBAdapter.**bulk_insert** (*table, items*)
 MongoDBAdapter.**check_fields_for_cmp** (*f*)
 MongoDBAdapter.**count** (*query, distinct=None, snapshot=True*)
 MongoDBAdapter.**create_table** (*table, migrate=True, fake_migrate=False, polymodel=None*)
 MongoDBAdapter.**delete** (*tablename, query, safe=None*)
 MongoDBAdapter.**driver_auto_json** = ['loads', 'dumps']
 MongoDBAdapter.**drivers** = ('pymongo',)
 MongoDBAdapter.**drop** (*table, mode=''*)
 MongoDBAdapter.**expand** (*expression, field_type=None*)
static MongoDBAdapter.**has_field** (*expression*)
 MongoDBAdapter.**insert** (*table, fields, safe=None*)
 Safe determines whether a asynchronous request is done or a synchronous action is done For safety, we use by default synchronous requests
 MongoDBAdapter.**needs_mongodb_aggregation_pipeline** (*f*)
 MongoDBAdapter.**object_id** (*arg=None*)
 Convert input to a valid Mongodb ObjectId instance
 self.object_id("<random>") -> ObjectId (not unique) instance
 MongoDBAdapter.**parse_blob** (*value, field_type*)
static MongoDBAdapter.**parse_data** (*expression, attribute, value=None*)
 MongoDBAdapter.**parse_id** (*value, field_type*)
 MongoDBAdapter.**parse_reference** (*value, field_type*)
 MongoDBAdapter.**represent** (*obj, fieldtype*)
 MongoDBAdapter.**select** (*query, fields, attributes, snapshot=False*)
 MongoDBAdapter.**truncate** (*table, mode, safe=None*)
 MongoDBAdapter.**types** = {'string': <type 'str'>, 'reference': <type 'long'>, 'text': <type 'str'>, 'id': <type 'long'>, 'f'
 MongoDBAdapter.**update** (*tablename, query, fields, safe=None*)
 MongoDBAdapter.**uploads_in_blob** = False
 MongoDBAdapter.**validate_second** (*f*)

pydal.adapters.mssql module

class pydal.adapters.mssql.**MSSQL2Adapter** (*db, uri, pool_size=0, folder=None, db_codec='UTF-8', credential_decoder=<function IDENTITY at 0x7f61150dc320>, driver_args={}, adapter_args={}, do_connect=True, srid=4326, after_connection=None*)
 Bases: pydal.adapters.mssql.MSSQLAdapter

ILIKE (*first, second, escape=None*)

Case insensitive like operator

drivers = ('pyodbc',)

execute (*a, **b)

represent (obj, fieldtype)

types = {'reference': 'INT %(null)s %(unique)s, CONSTRAINT %(constraint_name)s FOREIGN KEY %(field_name)s

```
class pydal.adapters.mssql.MSSQL3Adapter (db, uri, pool_size=0, folder=None, db_codec='UTF-8',
                                          credential_decoder=<function IDENTITY at 0x7f61150dc320>, driver_args={},
                                          adapter_args={}, do_connect=True, srid=4326,
                                          after_connection=None)
```

Bases: `pydal.adapters.mssql.MSSQLAdapter`

Experimental support for pagination in MSSQL

Requires MSSQL >= 2005, uses `ROW_NUMBER()`

rowslice (rows, minimum=0, maximum=None)

select_limitby (sql_s, sql_f, sql_t, sql_w, sql_o, limitby)

types = {'reference': 'INT %(null)s %(unique)s, CONSTRAINT %(constraint_name)s FOREIGN KEY %(field_name)s

```
class pydal.adapters.mssql.MSSQL3NAdapter (db, uri, pool_size=0, folder=None,
                                           db_codec='UTF-8',
                                           credential_decoder=<function IDENTITY at 0x7f61150dc320>,
                                           driver_args={},
                                           adapter_args={}, do_connect=True, srid=4326,
                                           after_connection=None)
```

Bases: `pydal.adapters.mssql.MSSQLNAdapter`

drivers = ('pyodbc',)

Experimental support for pagination in MSSQL Experimental: see `MSSQLNAdapter` docstring for warnings

Requires MSSQL >= 2005, uses `ROW_NUMBER()`

rowslice (rows, minimum=0, maximum=None)

select_limitby (sql_s, sql_f, sql_t, sql_w, sql_o, limitby)

types = {'reference': 'INT %(null)s %(unique)s, CONSTRAINT %(constraint_name)s FOREIGN KEY %(field_name)s

```
class pydal.adapters.mssql.MSSQL4Adapter (db, uri, pool_size=0, folder=None, db_codec='UTF-8',
                                          credential_decoder=<function IDENTITY at 0x7f61150dc320>, driver_args={},
                                          adapter_args={}, do_connect=True, srid=4326,
                                          after_connection=None)
```

Bases: `pydal.adapters.mssql.MSSQLAdapter`

Support for “native” pagination

Requires MSSQL >= 2012, uses `OFFSET ... ROWS ... FETCH NEXT ... ROWS ONLY`

rowslice (rows, minimum=0, maximum=None)

select_limitby (sql_s, sql_f, sql_t, sql_w, sql_o, limitby)

types = {'reference': 'INT %(null)s %(unique)s, CONSTRAINT %(constraint_name)s FOREIGN KEY %(field_name)s

```
class pydal.adapters.mssql.MSSQL4NAdapter (db, uri, pool_size=0, folder=None,
                                           db_codec='UTF-8', credential_decoder=<function IDENTITY at
                                           0x7f61150dc320>, driver_args={},
                                           adapter_args={}, do_connect=True, srid=4326,
                                           after_connection=None)
```

Bases: `pydal.adapters.mssql.MSSQLNAdapter`

Experimental: see `MSSQLNAdapter` docstring for warnings Support for “native” pagination

Unicode-compatible version Requires MSSQL >= 2012, uses `OFFSET ... ROWS ... FETCH NEXT ... ROWS ONLY` After careful testing, this should be the de-facto adapter for recent MSSQL backends

rowslice (*rows*, *minimum*=0, *maximum*=None)

select_limitby (*sql_s*, *sql_f*, *sql_t*, *sql_w*, *sql_o*, *limitby*)

types = {'reference': 'INT %(null)s %(unique)s, CONSTRAINT %(constraint_name)s FOREIGN KEY (%(field_name)s

```
class pydal.adapters.mssql.MSSQLAdapter (db, uri, pool_size=0, folder=None, db_codec='UTF-
8', credential_decoder=<function IDEN-
TITY at 0x7f61150dc320>, driver_args={},
adapter_args={}, do_connect=True, srid=4326,
after_connection=None)
```

Bases: `pydal.adapters.base.BaseAdapter`

AGGREGATE (*first*, *what*)

ALLOW_NULL ()

CAST (*first*, *second*)

CONCAT (**items*)

CONTAINS (*first*, *second*, *case_sensitive*=True)

ENDSWITH (*first*, *second*)

EPOCH (*first*)

EXTRACT (*field*, *what*)

FALSE = 0

ILIKE (*first*, *second*, *escape*=None)
Case insensitive like operator

LEFT_JOIN ()

LENGTH (*first*)

LIKE (*first*, *second*, *escape*=None)
Case sensitive like operator

PRIMARY_KEY (*key*)

QUOTE_TEMPLATE = “”%s””

RANDOM ()

REGEXP (*first*, *second*)

REGEX_ARGPATTERN = <_sre.SRE_Pattern object at 0x7f6114e8a370>

REGEX_DSN = <_sre.SRE_Pattern object at 0x7f6114e8dc00>

REGEX_URI = <_sre.SRE_Pattern object at 0x15a3560>


```

STARTSWITH (first, second)
ST_ASTEXT (first)
ST_CONTAINS (first, second)
ST_DISTANCE (first, second)
ST_EQUALS (first, second)
ST_INTERSECTS (first, second)
ST_OVERLAPS (first, second)
ST_TOUCHES (first, second)
ST_WITHIN (first, second)
SUBSTRING (field, parameters)
TRUE = 1
T_SEP = 'T'
concat_add (tablename)
drivers = ('pyodbc',)
lastrowid (table)
like_escaper_default (term)
mssql_like_normalizer (term)
represent (obj, fieldtype)
rowslice (rows, minimum=0, maximum=None)
select_limitby (sql_s, sql_f, sql_t, sql_w, sql_o, limitby)
types = {'reference': 'INT %(null)s %(unique)s, CONSTRAINT %(constraint_name)s FOREIGN KEY (%(field_name
varquote (name)
class pydal.adapters.mssql.MSSQLNAdapter (db, uri, pool_size=0, folder=None, db_codec='UTF-8', credential_decoder=<function IDENTITY at 0x7f61150dc320>, driver_args={}, adapter_args={}, do_connect=True, srid=4326, after_connection=None)
Bases: pydal.adapters.mssql.MSSQLAdapter
ILIKE (first, second, escape=None)
    Case insensitive like operator
drivers = ('pyodbc',)
    Experimental – base class for handling unicode in MSSQL by default. Needs lots of testing. Try this on a fresh (or on a legacy) database. Using this in a database handled previously with non-unicode aware adapter is NOT supported
execute (*a, **b)
represent (obj, fieldtype)
types = {'reference': 'INT %(null)s %(unique)s, CONSTRAINT %(constraint_name)s FOREIGN KEY (%(field_name

```

```
class pydal.adapters.mssql.SybaseAdapter (db, uri, pool_size=0, folder=None, db_codec='UTF-8', credential_decoder=<function IDENTITY at 0x7f61150dc320>, driver_args={}, adapter_args={}, do_connect=True, srid=4326, after_connection=None)

Bases: pydal.adapters.mssql.MSSQLAdapter

drivers = 'Sybase'

types = {'reference': 'INT NULL, CONSTRAINT %(constraint_name)s FOREIGN KEY (%(field_name)s) REFERENCEN
```

```
class pydal.adapters.mssql.VerticaAdapter (db, uri, pool_size=0, folder=None, db_codec='UTF-8', credential_decoder=<function IDENTITY at 0x7f61150dc320>, driver_args={}, adapter_args={}, do_connect=True, srid=4326, after_connection=None)

Bases: pydal.adapters.mssql.MSSQLAdapter

EXTRACT (first, what)

T_SEP = ' '

drivers = ('pyodbc',)

execute (a)

lastrowid (table)

select_limitby (sql_s, sql_f, sql_t, sql_w, sql_o, limitby)

types = {'big-reference': 'BIGINT REFERENCES %(foreign_key)s ON DELETE %(on_delete_action)s', 'string': 'VA
```

pydal.adapters.mysql module

```
class pydal.adapters.mysql.MySQLAdapter (db, uri, pool_size=0, folder=None, db_codec='UTF-8', credential_decoder=<function IDENTITY at 0x7f61150dc320>, driver_args={}, adapter_args={}, do_connect=True, after_connection=None)

Bases: pydal.adapters.base.BaseAdapter

CAST (first, second)

CONCAT (*items)

EPOCH (first)

QUOTE_TEMPLATE = "%s"

RANDOM ()

REGEXP (first, second)

REGEX_URI = <_sre.SRE_Pattern object at 0x14b9e10>

SUBSTRING (field, parameters)

after_connection ()

commit_on_alter_table = True

commit_prepared (key)

distributed_transaction_begin (key)
```

```

drivers = ('MySQLdb', 'pymysql', 'mysqlconnector')
prepare (key)
rollback_prepared (key)
support_distributed_transaction = True
types = {'reference': 'INT %(null)s %(unique)s, INDEX %(index_name)s (%(field_name)s), FOREIGN KEY (%(field_name)s) %(reference)s',
varquote (name)

```

pydal.adapters.oracle module

```

class pydal.adapters.oracle.OracleAdapter (db, uri, pool_size=0, folder=None, db_codec='UTF-8', credential_decoder=<function IDENTITY at 0x7f61150dc320>, driver_args={}, adapter_args={}, do_connect=True, after_connection=None)
    Bases: pydal.adapters.base.BaseAdapter
LEFT_JOIN ()
NOT_NULL (default, field_type)
RANDOM ()
REGEXP (first, second)
after_connection ()
commit_on_alter_table = False
constraint_name (tablename, fieldname)
create_sequence_and_triggers (query, table, **args)
drivers = ('cx_Oracle',)
execute (command, args=None)
lastrowid (table)
oracle_fix = <_sre.SRE_Pattern object at 0x7f6115187ab0>
represent_exceptions (obj, fieldtype)
select_limitby (sql_s, sql_f, sql_t, sql_w, sql_o, limitby)
sqlsafe_table (tablename, ot=None)
trigger_name (tablename)
types = {'reference': 'NUMBER, CONSTRAINT %(constraint_name)s FOREIGN KEY (%(field_name)s) REFERENC

```

pydal.adapters.postgres module

```
class pydal.adapters.postgres.JDBCPostgreSQLAdapter (db, uri, pool_size=0, folder=None,
                                                    db_codec='UTF-8', credential_decoder=<function IDENTITY at 0x7f61150dc320>,
                                                    driver_args={}, adapter_args={}, do_connect=True, after_connection=None)
```

Bases: `pydal.adapters.postgres.PostgreSQLAdapter`

REGEX_URI = `<_sre.SRE_Pattern object at 0x7f611512ec30>`

after_connection ()

drivers = ('zxJDBC',)

```
class pydal.adapters.postgres.NewPostgreSQLAdapter (db, uri, pool_size=0, folder=None,
                                                    db_codec='UTF-8', credential_decoder=<function IDENTITY at 0x7f61150dc320>,
                                                    driver_args={}, adapter_args={}, do_connect=True, srid=4326, after_connection=None)
```

Bases: `pydal.adapters.postgres.PostgreSQLAdapter`

ANY (*first*)

CONTAINS (*first, second, case_sensitive=True*)

EQ (*first, second=None*)

ILIKE (*first, second, escape=None*)

drivers = ('psycopg2', 'pg8000')

parse_list_integers (*value, field_type*)

parse_list_references (*value, field_type*)

parse_list_strings (*value, field_type*)

represent (*obj, fieldtype*)

types = {'reference': 'INTEGER REFERENCES %(foreign_key)s ON DELETE %(on_delete_action)s %(null)s %(union)s'}

```
class pydal.adapters.postgres.PostgreSQLAdapter (db, uri, pool_size=0, folder=None,
                                                  db_codec='UTF-8', credential_decoder=<function IDENTITY at 0x7f61150dc320>,
                                                  driver_args={}, adapter_args={}, do_connect=True, srid=4326, after_connection=None)
```

Bases: `pydal.adapters.base.BaseAdapter`

ADD (*first, second*)

ILIKE (*first, second, escape=None*)
Case sensitive like operator

LIKE (*first, second, escape=None*)
Case sensitive like operator

QUOTE_TEMPLATE = "'%s'"

RANDOM ()

REGEXP (*first, second*)

REGEX_URI = <_sre.SRE_Pattern object at 0x158a820>

ST_ASJSON (*first, second*)
http://postgis.org/docs/ST_AsJSON.html

ST_ASTEXT (*first*)
http://postgis.org/docs/ST_AsText.html

ST_CONTAINS (*first, second*)
http://postgis.org/docs/ST_Contains.html

ST_DISTANCE (*first, second*)
http://postgis.org/docs/ST_Distance.html

ST_DWITHIN (*first, tup*)
http://postgis.org/docs/ST_DWithin.html

ST_EQUALS (*first, second*)
http://postgis.org/docs/ST_Equals.html

ST_INTERSECTS (*first, second*)
http://postgis.org/docs/ST_Intersects.html

ST_OVERLAPS (*first, second*)
http://postgis.org/docs/ST_Overlaps.html

ST_SIMPLIFY (*first, second*)
http://postgis.org/docs/ST_Simplify.html

ST_SIMPLIFYPRESERVE TOPOLOGY (*first, second*)
http://postgis.org/docs/ST_SimplifyPreserveTopology.html

ST_TOUCHES (*first, second*)
http://postgis.org/docs/ST_Touches.html

ST_WITHIN (*first, second*)
http://postgis.org/docs/ST_Within.html

ST_X (*first*)
http://postgis.org/docs/ST_X.html

ST_Y (*first*)
http://postgis.org/docs/ST_Y.html

adapt (*obj*)

after_connection ()

commit_prepared (*key*)

create_sequence_and_triggers (*query, table, **args*)

distributed_transaction_begin (*key*)

drivers = ('psycpg2', 'pg8000')

execute (**a, **b*)

lastrowid (*table=None*)

prepare (*key*)

represent (*obj, fieldtype*)

rollback_prepared (*key*)

```
sequence_name (table)
support_distributed_transaction = True
try_json ()
types = {'reference': 'INTEGER REFERENCES %(foreign_key)s ON DELETE %(on_delete_action)s %(null)s %(unicod
varquote (name)
```

pydal.adapters.sapdb module

```
class pydal.adapters.sapdb.SAPDBAdapter (db, uri, pool_size=0, folder=None, db_codec='UTF-
8', credential_decoder=<function IDENTITY at
0x7f61150dc320>, driver_args={}, adapter_args={},
do_connect=True, after_connection=None)
Bases: pydal.adapters.base.BaseAdapter
REGEX_URI = <_sre.SRE_Pattern object at 0x158a820>
create_sequence_and_triggers (query, table, **args)
drivers = ('sapdb',)
lastrowid (table)
select_limitby (sql_s, sql_f, sql_t, sql_w, sql_o, limitby)
sequence_name (table)
support_distributed_transaction = False
types = {'reference': 'INT, FOREIGN KEY (%(field_name)s) REFERENCES %(foreign_key)s ON DELETE %(on_del
```

pydal.adapters.sqlite module

```
class pydal.adapters.sqlite.JDBCSQLiteAdapter (db, uri, pool_size=0, folder=None,
db_codec='UTF-8', credential_decoder=<function IDENTITY at
0x7f61150dc320>, driver_args={},
adapter_args={}, do_connect=True, af-
ter_connection=None)
Bases: pydal.adapters.sqlite.SQLiteAdapter
after_connection ()
drivers = ('zxJDBC_sqlite',)
execute (a)
class pydal.adapters.sqlite.SQLiteAdapter (db, uri, pool_size=0, folder=None,
db_codec='UTF-8', credential_decoder=<function IDENTITY at
0x7f61150dc320>, driver_args={},
adapter_args={}, do_connect=True, af-
ter_connection=None)
Bases: pydal.adapters.base.BaseAdapter
EXTRACT (field, what)
REGEXP (first, second)
after_connection ()
```

```

can_select_for_update = None
delete (tablename, query)
drivers = ('sqlite2', 'sqlite3')
select (query, fields, attributes)
    Simulate SELECT ... FOR UPDATE with BEGIN IMMEDIATE TRANSACTION. Note that the entire
    database, rather than one record, is locked (it will be locked eventually anyway by the following UPDATE).
static web2py_extract (lookup, s)
static web2py_regexp (expression, item)
class pydal.adapters.sqlite.SpatialLiteAdapter (db, uri, pool_size=0, folder=None,
                                                db_codec='UTF-8', credential_decoder=<function IDENTITY at
                                                0x7f61150dc320>, driver_args={},
                                                adapter_args={}, do_connect=True,
                                                srid=4326, after_connection=None)

Bases: pydal.adapters.sqlite.SQLiteAdapter
ST_ASJSON (first, second)
ST_ASTEXT (first)
ST_CONTAINS (first, second)
ST_DISTANCE (first, second)
ST_EQUALS (first, second)
ST_INTERSECTS (first, second)
ST_OVERLAPS (first, second)
ST_SIMPLIFY (first, second)
ST_TOUCHES (first, second)
ST_WITHIN (first, second)
after_connection ()
drivers = ('sqlite3', 'sqlite2')
represent (obj, fieldtype)
types = {'string': 'CHAR(%(length)s)', 'reference': 'INTEGER REFERENCES %(foreign_key)s ON DELETE %(on_c

```

pydal.adapters.teradata module

```

class pydal.adapters.teradata.TeradataAdapter (db, uri, pool_size=0, folder=None,
                                                db_codec='UTF-8', credential_decoder=<function IDENTITY at
                                                0x7f61150dc320>, driver_args={},
                                                adapter_args={}, do_connect=True, af
                                                ter_connection=None)

Bases: pydal.adapters.base.BaseAdapter
LEFT_JOIN ()
close (action='commit', really=True)
drivers = ('pyodbc',)

```

```
select_limitby (sql_s, sql_f, sql_t, sql_w, sql_o, limitby)
```

```
types = {'reference': 'INT', 'text': 'VARCHAR(2000)', 'float': 'REAL', 'datetime': 'TIMESTAMP', 'bigint': 'BIGINT'}
```

Module contents

```
pydal.adapters.GoogleDatastoreAdapter = None  
make the import available for BaseAdapter
```

1.1.2 pydal.helpers package

Submodules

pydal.helpers.classes module

```
class pydal.helpers.classes.BasicStorage (*args, **kwargs)
```

```
    Bases: object
```

```
    clear (*args, **kwargs)
```

```
    copy (*args, **kwargs)
```

```
    get (key, default=None)
```

```
    has_key (item)
```

```
    items ()
```

```
    iteritems ()
```

```
    iterkeys ()
```

```
    itervalues ()
```

```
    keys ()
```

```
    pop (*args, **kwargs)
```

```
    update (*args, **kwargs)
```

```
    values ()
```

```
class pydal.helpers.classes.DatabaseStoredFile (db, filename, mode)
```

```
    close ()
```

```
    close_connection ()
```

```
    escape (obj)
```

```
    static exists (db, filename)
```

```
    read (bytes)
```

```
    readline ()
```

```
    static try_create_web2py_filesystem (db)
```

```
    web2py_filesystems = set([])
```

```
    write (data)
```


class `pydal.helpers.classes.FakeCursor`

Bases: `object`

The Python Database API Specification has a `cursor()` method, which NoSql drivers generally don't support. If the exception in this function is taken then it likely means that some piece of functionality has not yet been implemented in the driver. And something is using the cursor.

<https://www.python.org/dev/peps/pep-0249/>

warn_bad_usage (*attr*)

class `pydal.helpers.classes.FakeDriver` (**args, **kwargs*)

Bases: `pydal.helpers.classes.BasicStorage`

close ()

commit ()

cursor ()

class `pydal.helpers.classes.MethodAdder` (*table*)

Bases: `object`

register (*method_name=None*)

class `pydal.helpers.classes.NullCursor`

Bases: `pydal.helpers.classes.FakeCursor`

lastrowid = 1

class `pydal.helpers.classes.NullDriver` (**args, **kwargs*)

Bases: `pydal.helpers.classes.FakeDriver`

class `pydal.helpers.classes.RecordDeleter` (*table, id*)

Bases: `object`

class `pydal.helpers.classes.RecordUpdater` (*colset, table, id*)

Bases: `object`

class `pydal.helpers.classes.Reference`

Bases: `long`

get (*key, default=None*)

`pydal.helpers.classes.Reference_pickler` (*data*)

`pydal.helpers.classes.Reference_unpickler` (*data*)

class `pydal.helpers.classes.SQLALL` (*table*)

Bases: `object`

Helper class providing a comma-separated string having all the field names (prefixed by table name and '.')

normally only called from within `gluon.dal`

class `pydal.helpers.classes.SQLCallableList`

Bases: `list`

class `pydal.helpers.classes.SQLCustomType` (*type='string', native=None, encoder=None, decoder=None, validator=None, _class=None, widget=None, represent=None*)

Bases: `object`

Allows defining of custom SQL types

Parameters

- **type** – the web2py type (default = ‘string’)
- **native** – the backend type
- **encoder** – how to encode the value to store it in the backend
- **decoder** – how to decode the value retrieved from the backend
- **validator** – what validators to use (default = None, will use the default validator for type)

Example:: Define as:

```
decimal = SQLCustomType( type = 'double', native = 'integer', encoder =(lambda x:
    int(float(x) * 100)), decoder = (lambda x: Decimal("0.00") + Decimal(str(float(x)/100)) )
)
db.define_table( 'example', Field('value', type=decimal) )
```

endswith (*text=None*)

startswith (*text=None*)

class pydal.helpers.classes.**Serializable**
Bases: object

as_dict (*flat=False, sanitize=True*)

as_json (*sanitize=True*)

as_xml (*sanitize=True*)

as_yaml (*sanitize=True*)

class pydal.helpers.classes.**UseDatabaseStoredFile**

file_close (*fileobj*)

file_delete (*filename*)

file_exists (*filename*)

file_open (*filename, mode='rb', lock=True*)

pydal.helpers.classes.**pickle_basicstorage** (*s*)

pydal.helpers.methods module

pydal.helpers.methods.**archive_record** (*qset, fs, archive_table, current_record*)

pydal.helpers.methods.**auto_represent** (*field*)

pydal.helpers.methods.**auto_validators** (*field*)

pydal.helpers.methods.**bar_decode_integer** (*value*)

pydal.helpers.methods.**bar_decode_string** (*value*)

pydal.helpers.methods.**bar_encode** (*items*)

pydal.helpers.methods.**bar_escape** (*item*)

pydal.helpers.methods.**cleanup** (*text*)

Validates that the given text is clean: only contains [0-9a-zA-Z_]

pydal.helpers.methods.**geoLine** (**line*)

```

pydal.helpers.methods.geoPoint (x, y)
pydal.helpers.methods.geoPolygon (*line)
pydal.helpers.methods.hide_password (uri)
pydal.helpers.methods.int2uuid (n)
pydal.helpers.methods.list_represent (values, row=None)
pydal.helpers.methods.pluralize (singular, rules=[(<_sre.SRE_Pattern object at
0x7f611834de00>, <_sre.SRE_Pattern object at
0x7f611834de00>, 'children'), (<_sre.SRE_Pattern ob-
ject at 0x7f61150f9190>, <_sre.SRE_Pattern object
at 0x7f61150f9190>, 'eet'), (<_sre.SRE_Pattern ob-
ject at 0x7f61183c0e70>, <_sre.SRE_Pattern object
at 0x7f61183c0e70>, 'eeth'), (<_sre.SRE_Pattern ob-
ject at 0x7f61183c0f30>, <_sre.SRE_Pattern object at
0x7f611834ded0>, '\Naves'), (<_sre.SRE_Pattern ob-
ject at 0x7f61150f9240>, <_sre.SRE_Pattern object
at 0x7f61150f9240>, 'ses'), (<_sre.SRE_Pattern ob-
ject at 0x7f61150f92f0>, <_sre.SRE_Pattern object
at 0x7f61150f92f0>, 'men'), (<_sre.SRE_Pattern ob-
ject at 0x7f61150f93a0>, <_sre.SRE_Pattern object
at 0x7f61150f93a0>, 'ives'), (<_sre.SRE_Pattern ob-
ject at 0x7f61150f9450>, <_sre.SRE_Pattern object
at 0x7f61150f9450>, 'eaux'), (<_sre.SRE_Pattern ob-
ject at 0x7f6118329cb0>, <_sre.SRE_Pattern object
at 0x7f6118329cb0>, 'lves'), (<_sre.SRE_Pattern ob-
ject at 0x7f61150fe030>, <_sre.SRE_Pattern object
at 0x7f6115845578>, 'es'), (<_sre.SRE_Pattern ob-
ject at 0x7f61150e02d0>, <_sre.SRE_Pattern object
at 0x7f6115845578>, 'es'), (<_sre.SRE_Pattern ob-
ject at 0x7f61183087f0>, <_sre.SRE_Pattern object
at 0x7f61150e1420>, 'ies'), (<_sre.SRE_Pattern ob-
ject at 0x7f6115845578>, <_sre.SRE_Pattern object at
0x7f6115845578>, 's')])
pydal.helpers.methods.smart_query (fields, text)
pydal.helpers.methods.use_common_filters (query)
pydal.helpers.methods.uuid2int (uidv)
pydal.helpers.methods.varquote_aux (name, quotestr='%s')
pydal.helpers.methods.xorify (orderby)

```

pydal.helpers.regex module

Module contents

1.2 Submodules

1.3 pydal.base module

This file is part of the web2py Web Framework

Copyrighted by Massimo Di Piero <mdipiero@cs.depaul.edu>
License: LGPLv3 (<http://www.gnu.org/licenses/lgpl.html>)

This file contains the DAL support for many relational databases, including:

- SQLite & SpatiaLite
- MySQL
- Postgres
- Firebird
- Oracle
- MS SQL
- DB2
- Interbase
- Ingres
- Informix (9+ and SE)
- SapDB (experimental)
- Cubrid (experimental)
- CouchDB (experimental)
- MongoDB (in progress)
- Google:nosql
- Google:sql
- Teradata
- IMAP (experimental)

Example of usage:

```
>>> # from dal import DAL, Field

### create DAL connection (and create DB if it doesn't exist)
>>> db = DAL('sqlite://storage.sqlite', 'mysql://a:b@localhost/x'),
... folder=None)

### define a table 'person' (create/alter as necessary)
>>> person = db.define_table('person', Field('name', 'string'))

### insert a record
>>> id = person.insert(name='James')

### retrieve it by id
>>> james = person(id)

### retrieve it by name
>>> james = person(name='James')

### retrieve it by arbitrary query
>>> query = (person.name=='James') & (person.name.startswith('J'))
```

```

>>> james = db(query).select(person.ALL)[0]

### update one record
>>> james.update_record(name='Jim')
<Row {'id': 1, 'name': 'Jim'}>

### update multiple records by query
>>> db(person.name.like('J%')).update(name='James')
1

### delete records by query
>>> db(person.name.lower() == 'jim').delete()
0

### retrieve multiple records (rows)
>>> people = db(person).select(orderby=person.name,
... groupby=person.name, limitby=(0,100))

### further filter them
>>> james = people.find(lambda row: row.name == 'James').first()
>>> print james.id, james.name
1 James

### check aggregates
>>> counter = person.id.count()
>>> print db(person).select(counter).first() (counter)
1

### delete one record
>>> james.delete_record()
1

### delete (drop) entire database table
>>> person.drop()

```

Supported DAL URI strings:

```

'sqlite://test.db'
'spatialite://test.db'
'sqlite:memory'
'spatialite:memory'
'jdbc:sqlite://test.db'
'mysql://root:none@localhost/test'
'postgres://mdipierro:password@localhost/test'
'postgres:psycopg2://mdipierro:password@localhost/test'
'postgres:pg8000://mdipierro:password@localhost/test'
'jdbc:postgres://mdipierro:none@localhost/test'
'mssql://web2py:none@A64X2/web2py_test'
'mssql2://web2py:none@A64X2/web2py_test' # alternate mappings
'mssql3://web2py:none@A64X2/web2py_test' # better pagination (requires >= 2005)
'mssql4://web2py:none@A64X2/web2py_test' # best pagination (requires >= 2012)
'oracle://username:password@database'
'firebird://user:password@server:3050/database'
'db2:ibm_db_dbi://DSN=dsn;UID=user;PWD=pass'
'db2:pyodbc://driver=DB2;hostname=host;database=database;uid=user;pwd=password;port=port.'
'firebird://username:password@hostname/database'
'firebird_embedded://username:password@c://path'
'informix://user:password@server:3050/database'

```

```
'informixu://user:password@server:3050/database' # unicode informix
'ingres://database' # or use an ODBC connection string, e.g. 'ingres://dsn=dsn_name'
'google:datastore' # for google app engine datastore (uses ndb by default)
'google:sql' # for google app engine with sql (mysql compatible)
'teradata://DSN=dsn;UID=user;PWD=pass; DATABASE=database' # experimental
'imap://user:password@server:port' # experimental
'mongodb://user:password@server:port/database' # experimental
```

For more info:

```
help(DAL)
help(Field)
```

```
class pydal.base.DAL (uri='sqlite://dummy.db', pool_size=0, folder=None, db_codec='UTF-8',
                      check_reserved=None, migrate=True, fake_migrate=False, migrate_enabled=True,
                      fake_migrate_all=False, decode_credentials=False, driver_args=None,
                      adapter_args=None, attempts=5, auto_import=False, bigint_id=False,
                      debug=False, lazy_tables=False, db_uid=None, do_connect=True,
                      after_connection=None, tables=None, ignore_field_case=True,
                      entity_quoting=False, table_hash=None)
```

Bases: `pydal.helpers.classes.Serializable`, `pydal.helpers.classes.BasicStorage`

An instance of this class represents a database connection

Parameters

- **uri** (*str*) – contains information for connecting to a database. Defaults to `'sqlite://dummy.db'`

Note: experimental: you can specify a dictionary as uri parameter i.e. with:

```
db = DAL({"uri": "sqlite://storage.sqlite",
         "tables": {...}, ...})
```

for an example of dict input you can check the output of the scaffolding db model with

```
db.as_dict()
```

Note that for compatibility with Python older than version 2.6.5 you should cast your dict input keys to str due to a syntax limitation on kwargs names. for proper DAL dictionary input you can use one of:

```
obj = serializers.cast_keys(dict, [encoding="utf-8"])
#or else (for parsing json input)
obj = serializers.loads_json(data, unicode_keys=False)
```

-
- **pool_size** – How many open connections to make to the database object.
 - **folder** – where .table files will be created. Automatically set within web2py. Use an explicit path when using DAL outside web2py
 - **db_codec** – string encoding of the database (default: 'UTF-8')
 - **table_hash** – database identifier with .tables. If your connection hash change you can still using old .tables if they have db_hash as prefix
 - **check_reserved** – list of adapters to check tablename and column names against sql/nosql reserved keywords. Defaults to *None*
 - 'common' List of sql keywords that are common to all database types such as "SELECT, INSERT". (recommended)

- 'all' Checks against all known SQL keywords
- '<adaptername>' Checks against the specific adapters list of keywords
- '<adaptername>_nonreserved' Checks against the specific adapters list of nonreserved keywords. (if available)
- **migrate** – sets default migrate behavior for all tables
- **fake_migrate** – sets default fake_migrate behavior for all tables
- **migrate_enabled** – If set to False disables ALL migrations
- **fake_migrate_all** – If set to True fake migrates ALL tables
- **attempts** – Number of times to attempt connecting
- **auto_import** – If set to True, tries import automatically table definitions from the databases folder (works only for simple models)
- **bigint_id** – If set, turn on bigint instead of int for id and reference fields
- **lazy_tables** – delaya table definition until table access
- **after_connection** – can a callable that will be executed after the connection

Example

Use as:

```
db = DAL('sqlite://test.db')
```

or:

```
db = DAL(**{"uri": ..., "tables": [...]}...) # experimental
```

```
db.define_table('tablename', Field('fieldname1'),
                Field('fieldname2'))
```

```
class Table (db, tablename, *fields, **args)
```

Bases: `pydal.helpers.classes.Serializable`, `pydal.helpers.classes.BasicStorage`

Represents a database table

Example::

You can create a table as:: `db = DAL(...)` `db.define_table('users', Field('name'))`

And then:

```
db.users.insert(name='me') # print db.users._insert(...) to see SQL
db.users.drop()
```

```
as_dict (flat=False, sanitize=True)
```

```
bulk_insert (items)
```

here items is a list of dictionaries

```
drop (mode='')
```

```
fields
```

```
import_from_csv_file (csvfile, id_map=None, null='<NULL>', unique='uuid',  
                      id_offset=None, *args, **kwargs)
```

Import records from csv file. Column headers must have same names as table fields. Field 'id' is ignored. If column names read 'table.file' the 'table.' prefix is ignored.

- 'unique' argument is a field which must be unique (typically a uuid field)
- 'restore' argument is default False; if set True will remove old values in table first.
- 'id_map' if set to None will not map ids

The import will keep the id numbers in the restored table. This assumes that there is an field of type id that is integer and in incrementing order. Will keep the id numbers in restored table.

```
insert (**fields)
```

```
on (query)
```

```
sqlsafe
```

```
sqlsafe_alias
```

```
truncate (mode=None)
```

```
update (*args, **kwargs)
```

```
update_or_insert (_key=<function <lambda> at 0x7f61150dc2a8>, **values)
```

```
validate_and_insert (**fields)
```

```
validate_and_update (_key=<function <lambda> at 0x7f61150dc2a8>, **fields)
```

```
validate_and_update_or_insert (_key=<function <lambda> at 0x7f61150dc2a8>,  
                               **fields)
```

```
with_alias (alias)
```

```
DAL.as_dict (flat=False, sanitize=True)
```

```
DAL.can_join ()
```

```
DAL.check_reserved_keyword (name)
```

Validates *name* against SQL keywords Uses self.check_reserve which is a list of operators to use.

```
DAL.close ()
```

```
DAL.commit ()
```

```
DAL.define_table (tablename, *fields, **args)
```

```
static DAL.distributed_transaction_begin (*instances)
```

```
static DAL.distributed_transaction_commit (*instances)
```

```
DAL.executesql (query, placeholders=None, as_dict=False, fields=None, colnames=None,  
              as_ordered_dict=False)
```

Executes an arbitrary query

Parameters

- **query** (*str*) – the query to submit to the backend
- **placeholders** – is optional and will always be None. If using raw SQL with placeholders, placeholders may be a sequence of values to be substituted in or, (if supported by the DB driver), a dictionary with keys matching named placeholders in your SQL.
- **as_dict** – will always be None when using DAL. If using raw SQL can be set to True and the results cursor returned by the DB driver will be converted to a sequence of dictionaries keyed with the db field names. Results returned with *as_dict=True* are the same as those returned when applying *.to_list()* to a DAL query. If "*as_ordered_dict=True*" the

behaviour is the same as when “as_dict”=True with the keys (field names) guaranteed to be in the same order as returned by the select name executed on the database.

- **fields** – list of DAL Fields that match the fields returned from the DB. The Field objects should be part of one or more Table objects defined on the DAL object. The “fields” list can include one or more DAL Table objects in addition to or instead of including Field objects, or it can be just a single table (not in a list). In that case, the Field objects will be extracted from the table(s).

Note: if either *fields* or *colnames* is provided, the results will be converted to a DAL *Rows* object using the *db._adapter.parse()* method

- **colnames** – list of field names in tablename.fieldname format

Note: It is also possible to specify both “fields” and the associated “colnames”. In that case, “fields” can also include DAL Expression objects in addition to Field objects. For Field objects in “fields”, the associated “colnames” must still be in tablename.fieldname format. For Expression objects in “fields”, the associated “colnames” can be any arbitrary labels.

DAL Table objects referred to by “fields” or “colnames” can be dummy tables and do not have to represent any real tables in the database. Also, note that the “fields” and “colnames” must be in the same order as the fields in the results cursor returned from the DB.

DAL.**export_to_csv_file** (*ofile*, **args*, ***kwargs*)

static DAL.**get_instances** ()

Returns a dictionary with uri as key with timings and defined tables:

```
{'sqlite://storage.sqlite': {
  'dbstats': [(select auth_user.email from auth_user, 0.02009)],
  'dbtables': {
    'defined': ['auth_cas', 'auth_event', 'auth_group',
               'auth_membership', 'auth_permission', 'auth_user'],
    'lazy': '[]'
  }
}
```

DAL.**has_representer** (*name*)

DAL.**import_from_csv_file** (*ifile*, *id_map=None*, *null='<NULL>'*, *unique='uuid'*,
map_tablenames=None, *ignore_missing_tables=False*, **args*,
***kwargs*)

DAL.**import_table_definitions** (*path*, *migrate=False*, *fake_migrate=False*, *tables=None*)

DAL.**lazy_define_table** (*tablename*, **fields*, ***args*)

DAL.**logger** = <logging.Logger object at 0x7f61150ba410>

DAL.**parse_as_rest** (*patterns*, *args*, *vars*, *queries=None*, *nested_select=True*)

Example

Use as:

```
db.define_table('person', Field('name'), Field('info'))
db.define_table('pet',
  Field('ownedby', db.person),
```

```
        Field('name'),Field('info')
    )

    @request.restful()
    def index():
        def GET(*args,**vars):
            patterns = [
                "/friends[person]",
               ("/{person.name}/:field",
               ("/{person.name}/pets[pet.ownedby]",
               ("/{person.name}/pets[pet.ownedby}/{pet.name}",
               ("/{person.name}/pets[pet.ownedby}/{pet.name}/:field",
                ("/dogs[pet]", db.pet.info=='dog'),
                ("/dogs[pet]/{pet.name.startswith}", db.pet.info=='dog'),
            ]
            parser = db.parse_as_rest(patterns,args,vars)
            if parser.status == 200:
                return dict(content=parser.response)
            else:
                raise HTTP(parser.status,parser.error)

        def POST(table_name,**vars):
            if table_name == 'person':
                return db.person.validate_and_insert(**vars)
            elif table_name == 'pet':
                return db.pet.validate_and_insert(**vars)
            else:
                raise HTTP(400)
        return locals()

DAL.represent(name,*args,**kwargs)
DAL.representers = {}
DAL.rollback()
DAL.serializers = None
static DAL.set_folder(folder)
DAL.smart_query(fields,text)
DAL.tables
DAL.uuid(x)
DAL.validators = None
DAL.validators_method = None
pydal.base.DAL_pickler(db)
pydal.base.DAL_unpickler(db_uid)
class pydal.base.MetaDAL
    Bases: type
```

1.4 pydal.connection module

class `pydal.connection.ConnectionPool`

Bases: `object`

POOLS = {}

after_connection()

after_connection_hook()

Hook for the `after_connection` parameter

check_active_connection = `True`

close (*action='commit', really=True*)

static close_all_instances (*action*)

to close cleanly databases in a multithreaded environment

find_or_make_work_folder()

reconnect (*f=None*)

Defines: `self.connection` and `self.cursor` if `self.pool_size>0` it will try pull the connection from the pool if the connection is not active (closed by db server) it will loop if not `self.pool_size` or no active connections in pool makes a new one

static set_folder (*folder*)

1.5 pydal.objects module

class `pydal.objects.BasicRows`

Bases: `object`

Abstract class for Rows and IterRows

__str__()

Serializes the table into a csv file

as_csv()

Serializes the table into a csv file

as_dict (*key='id', compact=True, storage_to_dict=True, datetime_to_str=False, custom_types=None*)

Returns the data as a dictionary of dictionaries (`storage_to_dict=True`) or records (`False`)

Parameters

- **key** – the name of the field to be used as dict key, normally the id
- **compact** – ? (default True)
- **storage_to_dict** – when True returns a dict, otherwise a list (default True)
- **datetime_to_str** – convert datetime fields as strings (default False)

as_json (*mode='object', default=None*)

Serializes the rows to a JSON list or object with objects `mode='object'` is not implemented (should return a nested object structure)

as_list (*compact=True, storage_to_dict=True, datetime_to_str=False, custom_types=None*)

Returns the data as a list or dictionary.

Parameters

- **storage_to_dict** – when True returns a dict, otherwise a list
- **datetime_to_str** – convert datetime fields as strings

as_trees (*parent_name='parent_id', children_name='children', render=False*)
returns the data as list of trees.

Parameters

- **parent_name** – the name of the field holding the reference to the parent (default parent_id).
- **children_name** – the name where the children of each row will be stored as a list (default children).
- **render** – whether we will render the fields using their represent (default False) can be a list of fields to render or True to render all.

as_xml (*row_name='row', rows_name='rows'*)

export_to_csv_file (*ofile, null='<NULL>', *args, **kwargs*)
Exports data to csv, the first line contains the column names

Parameters

- **ofile** – where the csv must be exported to
- **null** – how null values must be represented (default '<NULL>')
- **delimiter** – delimiter to separate values (default ',')
- **quotechar** – character to use to quote string values (default '"')
- **quoting** – quote system, use csv.QUOTE_*** (default csv.QUOTE_MINIMAL)
- **represent** – use the fields .represent value (default False)
- **colnames** – list of column names to use (default self.colnames)

This will only work when exporting rows objects!!!! DO NOT use this with db.export_to_csv()

json (*mode='object', default=None*)

Serializes the rows to a JSON list or object with objects mode='object' is not implemented (should return a nested object structure)

xml (*strict=False, row_name='row', rows_name='rows'*)

Serializes the table using sqlhtml.SQLTABLE (if present)

class pydal.objects.**Expression** (*db, op, first=None, second=None, type=None, **optional_args*)
Bases: object

abs ()

avg ()

belongs (**value, **kwattr*)

Accepts the following inputs:

```
field.belongs(1,2)
field.belongs((1,2))
field.belongs(query)
```

Does NOT accept:

```
field.belongs(1)
```

If the set you want back includes *None* values, you can do:

```
field.belongs((1, None), null=True)
```

coalesce (**others*)

coalesce_zero ()

contains (*value*, *all=False*, *case_sensitive=False*)

For GAE contains() is always case sensitive

day ()

endswith (*value*)

epoch ()

hour ()

ilike (*value*, *escape=None*)

len ()

like (*value*, *case_sensitive=True*, *escape=None*)

lower ()

max ()

min ()

minutes ()

month ()

regexp (*value*)

replace (*a*, *b*)

seconds ()

st_asgeojson (*precision=15*, *options=0*, *version=1*)

st_astext ()

st_contains (*value*)

st_distance (*other*)

st_dwithin (*value*, *distance*)

st_equals (*value*)

st_intersects (*value*)

st_overlaps (*value*)

st_simplify (*value*)

st_simplifypreservetopology (*value*)

st_touches (*value*)

st_within (*value*)

st_x ()

st_y ()

startswith (*value*)

sum()
upper()
with_alias (*alias*)
year()

class pydal.objects.**Field** (*fieldname*, *type*='string', *length*=None, *default*=<function <lambda> at 0x7f61150dc2a8>, *required*=False, *requires*=<function <lambda> at 0x7f61150dc2a8>, *ondelete*='CASCADE', *notnull*=False, *unique*=False, *uploadfield*=True, *widget*=None, *label*=None, *comment*=None, *writable*=True, *readable*=True, *update*=None, *authorize*=None, *autodelete*=False, *represent*=None, *uploadfolder*=None, *uploadseparate*=False, *uploadfs*=None, *compute*=None, *custom_store*=None, *custom_retrieve*=None, *custom_retrieve_file_properties*=None, *custom_delete*=None, *filter_in*=None, *filter_out*=None, *custom_qualifier*=None, *map_none*=None, *rname*=None)

Bases: pydal.objects.Expression, pydal.helpers.classes.Serializable

Lazy

Represents a database field

Example

Usage:

```
a = Field(name, 'string', length=32, default=None, required=False,
         requires=IS_NOT_EMPTY(), ondelete='CASCADE',
         notnull=False, unique=False,
         uploadfield=True, widget=None, label=None, comment=None,
         uploadfield=True, # True means store on disk,
                           # 'a_field_name' means store in this field in db
                           # False means file content will be discarded.
         writable=True, readable=True, update=None, authorize=None,
         autodelete=False, represent=None, uploadfolder=None,
         uploadseparate=False # upload to separate directories by uuid_keys
                              # first 2 character and tablename.fieldname
                              # False - old behavior
                              # True - put uploaded file in
                              # <uploaddir>/<tablename>.<fieldname>/uuid_key[:2]
                              # directory)
         uploadfs=None      # a pyfilesystem where to store upload
         )
```

to be used as argument of *DAL.define_table*

alias of `FieldMethod`

Method

alias of `FieldMethod`

Virtual

alias of `FieldVirtual`

as_dict (*flat*=False, *sanitize*=True)

clone (*point_self_references_to*=False, ***args*)

count (*distinct*=None)

```

formatter (value)
retrieve (name, path=None, nameonly=False)
    If nameonly==True return (filename, fullfilename) instead of (filename, stream)
retrieve_file_properties (name, path=None)
set_attributes (*args, **attributes)
sqlsafe
sqlsafe_name
store (file, filename=None, path=None)
validate (value)
class pydal.objects.FieldMethod (name, f=None, handler=None)
    Bases: object
class pydal.objects.FieldVirtual (name, f=None, ftype='string', label=None, table_name=None)
    Bases: object
class pydal.objects.IterRows (db, sql, fields, colnames, blob_decode, cacheable)
    Bases: pydal.objects.BasicRows
    first ()
    next ()
class pydal.objects.LazyReferenceGetter (table, id)
    Bases: object
class pydal.objects.LazySet (field, id)
    Bases: object
    count (distinct=None, cache=None)
    delete ()
    delete_uploaded_files (upload_fields=None)
    isempty ()
    nested_select (*fields, **attributes)
    select (*fields, **attributes)
    update (**update_fields)
    update_naive (**update_fields)
    validate_and_update (**update_fields)
class pydal.objects.Query (db, op, first=None, second=None, ignore_common_filters=False, **optional_args)
    Bases: pydal.helpers.classes.Serializable
    Necessary to define a set. It can be stored or can be passed to DAL.__call__() to obtain a Set

```

Example

Use as:

```
query = db.users.name=='Max'  
set = db(query)  
records = set.select()
```

as_dict (*flat=False, sanitize=True*)
Experimental stuff

This allows to return a plain dictionary with the basic query representation. Can be used with json/xml services for client-side db I/O

Example

Usage:

```
q = db.auth_user.id != 0  
q.as_dict(flat=True)  
{  
  "op": "NE",  
  "first": {  
    "tablename": "auth_user",  
    "fieldname": "id"  
  },  
  "second": 0  
}
```

case (*t=1, f=0*)

class `pydal.objects.Row` (**args, **kwargs*)
Bases: `pydal.helpers.classes.BasicStorage`

A dictionary that lets you do `d['a']` as well as `d.a` this is only used to store a *Row*

as_dict (*datetime_to_str=False, custom_types=None*)

as_json (*mode='object', default=None, colnames=None, serialize=True, **kwargs*)
serializes the row to a JSON object `kwargs` are passed to `.as_dict` method only “object” mode supported

serialize = False used by `Rows.as_json`

TODO: return array mode with query column order

mode and `colnames` are not implemented

as_xml (*row_name='row', colnames=None, indent=' '*)

get (*key, default=None*)

class `pydal.objects.Rows` (*db=None, records=[], colnames=[], compact=True, rawrows=None*)
Bases: `pydal.objects.BasicRows`

A wrapper for the return value of a select. It basically represents a table. It has an iterator and each row is represented as a *Row* dictionary.

__iter__ ()
Iterator over records

column (*column=None*)

exclude (*f*)
Removes elements from the calling `Rows` object, filtered by the function *f*, and returns a new `Rows` object containing the removed elements

find (*f*, *limitby=None*)

Returns a new Rows object, a subset of the original object, filtered by the function *f*

first ()

group_by_value (**fields*, ***args*)

Regroups the rows, by one of the fields

last ()

render (*i=None*, *fields=None*)

Takes an index and returns a copy of the indexed row with values transformed via the “represent” attributes of the associated fields.

Parameters

- **i** – index. If not specified, a generator is returned for iteration over all the rows.
- **fields** – a list of fields to transform (if None, all fields with “represent” attributes will be transformed)

setvirtualfields (***keyed_virtualfields*)

For reference:

```
db.define_table('x',Field('number','integer'))
if db(db.x).isempty(): [db.x.insert(number=i) for i in range(10)]

from gluon.dal import lazy_virtualfield

class MyVirtualFields(object):
    # normal virtual field (backward compatible, discouraged)
    def normal_shift(self): return self.x.number+1
    # lazy virtual field (because of @staticmethod)
    @lazy_virtualfield
    def lazy_shift(instance,row,delta=4): return row.x.number+delta
db.x.virtualfields.append(MyVirtualFields())

for row in db(db.x).select():
    print row.number, row.normal_shift, row.lazy_shift(delta=7)
```

sort (*f*, *reverse=False*)

Returns a list of sorted elements (not sorted in place)

class `pydal.objects.Set` (*db*, *query*, *ignore_common_filters=None*)

Bases: `pydal.helpers.classes.Serializable`

Represents a set of records in the database. Records are identified by the *query=Query(...)* object. Normally the Set is generated by *DAL.__call__(Query(...))*

Given a set, for example:

```
myset = db(db.users.name=='Max')
```

you can:

```
myset.update(db.users.name='Massimo')
myset.delete() # all elements in the set
myset.select(orderby=db.users.id, groupby=db.users.name, limitby=(0,10))
```

and take subsets:

```
subset = myset(db.users.id<5)
```

as_dict (*flat=False*, *sanitize=True*)

build (*d*)

Experimental: see `.parse()`

count (*distinct=None, cache=None*)

delete ()

delete_uploaded_files (*upload_fields=None*)

isempty ()

iterselect (**fields, **attributes*)

nested_select (**fields, **attributes*)

parse (*dquery*)

Experimental: Turn a dictionary into a Query object

select (**fields, **attributes*)

update (***update_fields*)

update_naive (***update_fields*)

Same as update but does not call `table._before_update` and `_after_update`

validate_and_update (***update_fields*)

class `pydal.objects.Table` (*db, tablename, *fields, **args*)

Bases: `pydal.helpers.classes.Serializable`, `pydal.helpers.classes.BasicStorage`

Represents a database table

Example::

You can create a table as:: `db = DAL(...)` `db.define_table('users', Field('name'))`

And then:

```
db.users.insert(name='me') # print db.users._insert(...) to see SQL
db.users.drop()
```

as_dict (*flat=False, sanitize=True*)

bulk_insert (*items*)

here items is a list of dictionaries

drop (*mode=''*)

fields

import_from_csv_file (*csvfile, id_map=None, null='<NULL>', unique='uuid', id_offset=None, *args, **kwargs*)

Import records from csv file. Column headers must have same names as table fields. Field 'id' is ignored. If column names read 'table.file' the 'table.' prefix is ignored.

- 'unique' argument is a field which must be unique (typically a uuid field)
- 'restore' argument is default False; if set True will remove old values in table first.
- 'id_map' if set to None will not map ids

The import will keep the id numbers in the restored table. This assumes that there is a field of type id that is integer and in incrementing order. Will keep the id numbers in restored table.

insert (***fields*)

on (*query*)

```
sqlsafe  
sqlsafe_alias  
truncate (mode=None)  
update (*args, **kwargs)  
update_or_insert (_key=<function <lambda> at 0x7f61150dc2a8>, **values)  
validate_and_insert (**fields)  
validate_and_update (_key=<function <lambda> at 0x7f61150dc2a8>, **fields)  
validate_and_update_or_insert (_key=<function <lambda> at 0x7f61150dc2a8>, **fields)  
with_alias (alias)  
class pydal.objects.VirtualCommand (method, row)  
    Bases: object  
pydal.objects.pickle_row (s)
```

1.6 Module contents

p

- pydal, 47
- pydal.adapters, 28
- pydal.adapters.base, 3
- pydal.adapters.couchdb, 9
- pydal.adapters.cubrid, 10
- pydal.adapters.db2, 10
- pydal.adapters.firebird, 10
- pydal.adapters.imap, 11
- pydal.adapters.informix, 15
- pydal.adapters.ingres, 15
- pydal.adapters.mongo, 16
- pydal.adapters.mssql, 18
- pydal.adapters.mysql, 22
- pydal.adapters.oracle, 23
- pydal.adapters.postgres, 24
- pydal.adapters.sapdb, 26
- pydal.adapters.sqlite, 26
- pydal.adapters.teradata, 27
- pydal.base, 31
- pydal.connection, 39
- pydal.helpers, 31
- pydal.helpers.classes, 28
- pydal.helpers.methods, 30
- pydal.helpers.regex, 31
- pydal.objects, 39

Symbols

`__iter__()` (pydal.objects.Rows method), 44
`__str__()` (pydal.objects.BasicRows method), 39

A

`abs()` (pydal.objects.Expression method), 40
`adapt()` (pydal.adapters.base.BaseAdapter method), 5
`adapt()` (pydal.adapters.postgres.PostgreSQLAdapter method), 25
AdapterMeta (class in pydal.adapters.base), 3
`ADD()` (pydal.adapters.base.BaseAdapter method), 3
`ADD()` (pydal.adapters.base.NoSQLAdapter method), 7
`ADD()` (pydal.adapters.mongo.MongoDBAdapter method), 16
`ADD()` (pydal.adapters.postgres.PostgreSQLAdapter method), 24
`after_connection()` (pydal.adapters.cubrid.CubridAdapter method), 10
`after_connection()` (pydal.adapters.mysql.MySQLAdapter method), 22
`after_connection()` (pydal.adapters.oracle.OracleAdapter method), 23
`after_connection()` (pydal.adapters.postgres.JDBCPostgreSQLAdapter method), 24
`after_connection()` (pydal.adapters.postgres.PostgreSQLAdapter method), 25
`after_connection()` (pydal.adapters.sqlite.JDBCSQLiteAdapter method), 26
`after_connection()` (pydal.adapters.sqlite.SpatialLiteAdapter method), 27
`after_connection()` (pydal.adapters.sqlite.SQLiteAdapter method), 26
`after_connection()` (pydal.connection.ConnectionPool method), 39
`after_connection_hook()` (pydal.connection.ConnectionPool method), 39
`AGGREGATE()` (pydal.adapters.base.BaseAdapter method), 3
`AGGREGATE()` (pydal.adapters.base.NoSQLAdapter method), 7
`AGGREGATE()` (pydal.adapters.mongo.MongoDBAdapter method), 16
`AGGREGATE()` (pydal.adapters.mssql.MSSQLAdapter method), 20
`alias()` (pydal.adapters.base.BaseAdapter method), 5
`ALLOW_NULL()` (pydal.adapters.base.BaseAdapter method), 3
`ALLOW_NULL()` (pydal.adapters.mssql.MSSQLAdapter method), 20
`AND()` (pydal.adapters.base.BaseAdapter method), 3
`AND()` (pydal.adapters.base.NoSQLAdapter method), 7
`AND()` (pydal.adapters.couchdb.CouchDBAdapter method), 9
`AND()` (pydal.adapters.imap.IMAPAdapter method), 13
`AND()` (pydal.adapters.mongo.MongoDBAdapter method), 16
`annotate_expression()` (pydal.adapters.mongo.MongoDBAdapter.Expanded method), 17
`ANY()` (pydal.adapters.postgres.NewPostgreSQLAdapter method), 24
`archive_record()` (in module pydal.helpers.methods), 30
`AS()` (pydal.adapters.base.BaseAdapter method), 3
`AS()` (pydal.adapters.base.NoSQLAdapter method), 7
`AS()` (pydal.adapters.mongo.MongoDBAdapter method), 16
`as_csv()` (pydal.objects.BasicRows method), 39
`as_dict()` (pydal.base.DAL method), 36
`as_dict()` (pydal.base.DAL.Table method), 35
`as_dict()` (pydal.helpers.classes.Serializable method), 30
`as_dict()` (pydal.objects.BasicRows method), 39
`as_dict()` (pydal.objects.Field method), 42
`as_dict()` (pydal.objects.Query method), 44
`as_dict()` (pydal.objects.Row method), 44
`as_dict()` (pydal.objects.Set method), 45
`as_dict()` (pydal.objects.Table method), 46
`as_json()` (pydal.helpers.classes.Serializable method), 30
`as_json()` (pydal.objects.BasicRows method), 39
`as_json()` (pydal.objects.Row method), 44

- as_list() (pydal.objects.BasicRows method), 39
 - AS_MARK (pydal.adapters.mongo.MongoDBAdapter attribute), 16
 - as_trees() (pydal.objects.BasicRows method), 40
 - as_xml() (pydal.helpers.classes.Serializable method), 30
 - as_xml() (pydal.objects.BasicRows method), 40
 - as_xml() (pydal.objects.Row method), 44
 - as_yaml() (pydal.helpers.classes.Serializable method), 30
 - auto_represent() (in module pydal.helpers.methods), 30
 - auto_validators() (in module pydal.helpers.methods), 30
 - avg() (pydal.objects.Expression method), 40
- ## B
- bar_decode_integer() (in module pydal.helpers.methods), 30
 - bar_decode_string() (in module pydal.helpers.methods), 30
 - bar_encode() (in module pydal.helpers.methods), 30
 - bar_escape() (in module pydal.helpers.methods), 30
 - BaseAdapter (class in pydal.adapters.base), 3
 - BasicRows (class in pydal.objects), 39
 - BasicStorage (class in pydal.helpers.classes), 28
 - BELONGS() (pydal.adapters.base.BaseAdapter method), 3
 - BELONGS() (pydal.adapters.imap.IMAPAdapter method), 13
 - BELONGS() (pydal.adapters.mongo.MongoDBAdapter method), 16
 - belongs() (pydal.objects.Expression method), 40
 - Binary (class in pydal.adapters.mongo), 16
 - build() (pydal.objects.Set method), 46
 - build_parsemap() (pydal.adapters.base.BaseAdapter method), 5
 - bulk_insert() (pydal.adapters.base.BaseAdapter method), 5
 - bulk_insert() (pydal.adapters.mongo.MongoDBAdapter method), 18
 - bulk_insert() (pydal.base.DAL.Table method), 35
 - bulk_insert() (pydal.objects.Table method), 46
- ## C
- can_join() (pydal.adapters.base.BaseAdapter method), 5
 - can_join() (pydal.adapters.base.NoSQLAdapter method), 8
 - can_join() (pydal.base.DAL method), 36
 - can_select_for_update (pydal.adapters.base.BaseAdapter attribute), 5
 - can_select_for_update (pydal.adapters.base.NoSQLAdapter attribute), 8
 - can_select_for_update (pydal.adapters.sqlite.SQLiteAdapter attribute), 26
 - CASE() (pydal.adapters.base.BaseAdapter method), 3
 - CASE() (pydal.adapters.mongo.MongoDBAdapter method), 16
 - case() (pydal.objects.Query method), 44
 - CAST() (pydal.adapters.base.BaseAdapter method), 3
 - CAST() (pydal.adapters.mssql.MSSQLAdapter method), 20
 - CAST() (pydal.adapters.mysql.MySQLAdapter method), 22
 - check_active_connection (pydal.connection.ConnectionPool attribute), 39
 - check_fields_for_cmp() (pydal.adapters.mongo.MongoDBAdapter method), 18
 - check_reserved_keyword() (pydal.base.DAL method), 36
 - cleanup() (in module pydal.helpers.methods), 30
 - clear() (pydal.helpers.classes.BasicStorage method), 28
 - clone() (pydal.objects.Field method), 42
 - close() (pydal.adapters.teradata.TeradataAdapter method), 27
 - close() (pydal.base.DAL method), 36
 - close() (pydal.connection.ConnectionPool method), 39
 - close() (pydal.helpers.classes.DatabaseStoredFile method), 28
 - close() (pydal.helpers.classes.FakeDriver method), 29
 - close_all_instances() (pydal.connection.ConnectionPool static method), 39
 - close_connection() (pydal.adapters.base.BaseAdapter method), 5
 - close_connection() (pydal.adapters.base.NoSQLAdapter method), 8
 - close_connection() (pydal.helpers.classes.DatabaseStoredFile method), 28
 - CMP_OPS_AGGREGATION_PIPELINE() (pydal.adapters.mongo.MongoDBAdapter method), 16
 - COALESCE() (pydal.adapters.base.BaseAdapter method), 3
 - coalesce() (pydal.objects.Expression method), 41
 - COALESCE_ZERO() (pydal.adapters.base.BaseAdapter method), 3
 - coalesce_zero() (pydal.objects.Expression method), 41
 - column() (pydal.objects.Rows method), 44
 - COMMA() (pydal.adapters.base.BaseAdapter method), 4
 - COMMA() (pydal.adapters.couchdb.CouchDBAdapter method), 9
 - COMMA() (pydal.adapters.mongo.MongoDBAdapter method), 16
 - commit() (pydal.adapters.base.BaseAdapter method), 5
 - commit() (pydal.adapters.base.NoSQLAdapter method), 8
 - commit() (pydal.base.DAL method), 36
 - commit() (pydal.helpers.classes.FakeDriver method), 29

- commit_on_alter_table (pydal.adapters.base.BaseAdapter attribute), 5
- commit_on_alter_table (pydal.adapters.firebird.FireBirdAdapter attribute), 11
- commit_on_alter_table (pydal.adapters.mysql.MySQLAdapter attribute), 22
- commit_on_alter_table (pydal.adapters.oracle.OracleAdapter attribute), 23
- commit_prepared() (pydal.adapters.base.BaseAdapter method), 5
- commit_prepared() (pydal.adapters.base.NoSQLAdapter method), 8
- commit_prepared() (pydal.adapters.mysql.MySQLAdapter method), 22
- commit_prepared() (pydal.adapters.postgres.PostgreSQLAdapter method), 25
- common_filter() (pydal.adapters.base.BaseAdapter method), 5
- CONCAT() (pydal.adapters.base.BaseAdapter method), 4
- CONCAT() (pydal.adapters.mssql.MSSQLAdapter method), 20
- CONCAT() (pydal.adapters.mysql.MySQLAdapter method), 22
- concat_add() (pydal.adapters.base.BaseAdapter method), 5
- concat_add() (pydal.adapters.base.NoSQLAdapter method), 8
- concat_add() (pydal.adapters.mssql.MSSQLAdapter method), 21
- connection (pydal.adapters.base.BaseAdapter attribute), 5
- ConnectionPool (class in pydal.connection), 39
- connector() (pydal.adapters.base.BaseAdapter method), 5
- constraint_name() (pydal.adapters.base.BaseAdapter method), 5
- constraint_name() (pydal.adapters.base.NoSQLAdapter method), 8
- constraint_name() (pydal.adapters.oracle.OracleAdapter method), 23
- CONTAINS() (pydal.adapters.base.BaseAdapter method), 4
- CONTAINS() (pydal.adapters.firebird.FireBirdAdapter method), 10
- CONTAINS() (pydal.adapters.imap.IMAPAdapter method), 13
- CONTAINS() (pydal.adapters.mongo.MongoDBAdapter method), 16
- CONTAINS() (pydal.adapters.mssql.MSSQLAdapter method), 20
- CONTAINS() (pydal.adapters.postgres.NewPostgreSQLAdapter method), 24
- contains() (pydal.objects.Expression method), 41
- convert_date() (pydal.adapters.imap.IMAPAdapter method), 14
- copy() (pydal.helpers.classes.BasicStorage method), 28
- CouchDBAdapter (class in pydal.adapters.couchdb), 9
- COUNT() (pydal.adapters.base.BaseAdapter method), 4
- count() (pydal.adapters.base.BaseAdapter method), 5
- count() (pydal.adapters.couchdb.CouchDBAdapter method), 9
- count() (pydal.adapters.imap.IMAPAdapter method), 14
- COUNT() (pydal.adapters.mongo.MongoDBAdapter method), 16
- count() (pydal.adapters.mongo.MongoDBAdapter method), 18
- count() (pydal.objects.Field method), 42
- count() (pydal.objects.LazySet method), 43
- count() (pydal.objects.Set method), 46
- create_sequence_and_triggers() (pydal.adapters.base.BaseAdapter method), 5
- create_sequence_and_triggers() (pydal.adapters.base.NoSQLAdapter method), 8
- create_sequence_and_triggers() (pydal.adapters.firebird.FireBirdAdapter method), 11
- create_sequence_and_triggers() (pydal.adapters.ingres.IngresAdapter method), 15
- create_sequence_and_triggers() (pydal.adapters.oracle.OracleAdapter method), 23
- create_sequence_and_triggers() (pydal.adapters.postgres.PostgreSQLAdapter method), 25
- create_sequence_and_triggers() (pydal.adapters.sapdb.SAPDBAdapter method), 26
- create_table() (pydal.adapters.base.BaseAdapter method), 5
- create_table() (pydal.adapters.couchdb.CouchDBAdapter method), 9
- create_table() (pydal.adapters.imap.IMAPAdapter method), 14
- create_table() (pydal.adapters.mongo.MongoDBAdapter method), 18
- CubridAdapter (class in pydal.adapters.cubrid), 10
- cursor() (pydal.helpers.classes.FakeDriver method), 29

D

- DAL (class in pydal.base), 34
- DAL.Table (class in pydal.base), 35

- DAL_pickler() (in module pydal.base), 38
- DAL_unpickler() (in module pydal.base), 38
- DatabaseStoredFile (class in pydal.helpers.classes), 28
- day() (pydal.objects.Expression method), 41
- DB2Adapter (class in pydal.adapters.db2), 10
- dbengine (pydal.adapters.imap.IMAPAdapter attribute), 14
- dbpath (pydal.adapters.base.BaseAdapter attribute), 5
- decode() (pydal.adapters.mongo.MongoBlob static method), 16
- define_table() (pydal.base.DAL method), 36
- define_tables() (pydal.adapters.imap.IMAPAdapter method), 14
- delete() (pydal.adapters.base.BaseAdapter method), 5
- delete() (pydal.adapters.couchdb.CouchDBAdapter method), 9
- delete() (pydal.adapters.imap.IMAPAdapter method), 14
- delete() (pydal.adapters.mongo.MongoDBAdapter method), 18
- delete() (pydal.adapters.sqlite.SQLiteAdapter method), 27
- delete() (pydal.objects.LazySet method), 43
- delete() (pydal.objects.Set method), 46
- delete_uploaded_files() (pydal.objects.LazySet method), 43
- delete_uploaded_files() (pydal.objects.Set method), 46
- distributed_transaction_begin() (pydal.adapters.base.BaseAdapter method), 5
- distributed_transaction_begin() (pydal.adapters.base.NoSQLAdapter method), 8
- distributed_transaction_begin() (pydal.adapters.mysql.MySQLAdapter method), 22
- distributed_transaction_begin() (pydal.adapters.postgres.PostgreSQLAdapter method), 25
- distributed_transaction_begin() (pydal.base.DAL static method), 36
- distributed_transaction_commit() (pydal.base.DAL static method), 36
- DIV() (pydal.adapters.base.BaseAdapter method), 4
- DIV() (pydal.adapters.base.NoSQLAdapter method), 8
- DIV() (pydal.adapters.mongo.MongoDBAdapter method), 16
- driver (pydal.adapters.base.BaseAdapter attribute), 5
- driver_auto_json (pydal.adapters.base.BaseAdapter attribute), 5
- driver_auto_json (pydal.adapters.mongo.MongoDBAdapter attribute), 18
- driver_name (pydal.adapters.base.BaseAdapter attribute), 5
- drivers (pydal.adapters.base.BaseAdapter attribute), 5
- drivers (pydal.adapters.couchdb.CouchDBAdapter attribute), 9
- drivers (pydal.adapters.cubrid.CubridAdapter attribute), 10
- drivers (pydal.adapters.db2.DB2Adapter attribute), 10
- drivers (pydal.adapters.firebird.FireBirdAdapter attribute), 11
- drivers (pydal.adapters.firebird.FireBirdEmbeddedAdapter attribute), 11
- drivers (pydal.adapters.imap.IMAPAdapter attribute), 14
- drivers (pydal.adapters.informix.InformixAdapter attribute), 15
- drivers (pydal.adapters.ingres.IngresAdapter attribute), 15
- drivers (pydal.adapters.ingres.IngresUnicodeAdapter attribute), 16
- drivers (pydal.adapters.mongo.MongoDBAdapter attribute), 18
- drivers (pydal.adapters.mssql.MSSQL2Adapter attribute), 19
- drivers (pydal.adapters.mssql.MSSQL3NAdapter attribute), 19
- drivers (pydal.adapters.mssql.MSSQLAdapter attribute), 21
- drivers (pydal.adapters.mssql.MSSQLNAdapter attribute), 21
- drivers (pydal.adapters.mssql.SybaseAdapter attribute), 22
- drivers (pydal.adapters.mssql.VerticaAdapter attribute), 22
- drivers (pydal.adapters.mysql.MySQLAdapter attribute), 22
- drivers (pydal.adapters.oracle.OracleAdapter attribute), 23
- drivers (pydal.adapters.postgres.JDBCPostgreSQLAdapter attribute), 24
- drivers (pydal.adapters.postgres.NewPostgreSQLAdapter attribute), 24
- drivers (pydal.adapters.postgres.PostgreSQLAdapter attribute), 25
- drivers (pydal.adapters.sapdb.SAPDBAdapter attribute), 26
- drivers (pydal.adapters.sqlite.JDBCSQLiteAdapter attribute), 26
- drivers (pydal.adapters.sqlite.SpatialLiteAdapter attribute), 27
- drivers (pydal.adapters.sqlite.SQLiteAdapter attribute), 27
- drivers (pydal.adapters.teradata.TeradataAdapter attribute), 27
- drop() (pydal.adapters.base.BaseAdapter method), 5
- drop() (pydal.adapters.base.NoSQLAdapter method), 8
- drop() (pydal.adapters.mongo.MongoDBAdapter method), 18

drop() (pydal.base.DAL.Table method), 35

drop() (pydal.objects.Table method), 46

E

encode_text() (pydal.adapters.imap.IMAPAdapter method), 14

ENDSWITH() (pydal.adapters.base.BaseAdapter method), 4

ENDSWITH() (pydal.adapters.base.NoSQLAdapter method), 8

ENDSWITH() (pydal.adapters.mongo.MongoDBAdapter method), 16

ENDSWITH() (pydal.adapters.mssql.MSSQLAdapter method), 20

endswith() (pydal.helpers.classes.SQLCustomType method), 30

endswith() (pydal.objects.Expression method), 41

EPOCH() (pydal.adapters.base.BaseAdapter method), 4

EPOCH() (pydal.adapters.firebird.FireBirdAdapter method), 10

EPOCH() (pydal.adapters.mongo.MongoDBAdapter method), 16

EPOCH() (pydal.adapters.mssql.MSSQLAdapter method), 20

EPOCH() (pydal.adapters.mysql.MySQLAdapter method), 22

epoch() (pydal.objects.Expression method), 41

EQ() (pydal.adapters.base.BaseAdapter method), 4

EQ() (pydal.adapters.couchdb.CouchDBAdapter method), 9

EQ() (pydal.adapters.imap.IMAPAdapter method), 13

EQ() (pydal.adapters.mongo.MongoDBAdapter method), 16

EQ() (pydal.adapters.postgres.NewPostgreSQLAdapter method), 24

escape() (pydal.helpers.classes.DatabaseStoredFile method), 28

exclude() (pydal.objects.Rows method), 44

execute() (pydal.adapters.base.BaseAdapter method), 5

execute() (pydal.adapters.base.NoSQLAdapter method), 8

execute() (pydal.adapters.db2.DB2Adapter method), 10

execute() (pydal.adapters.informix.InformixAdapter method), 15

execute() (pydal.adapters.mssql.MSSQL2Adapter method), 19

execute() (pydal.adapters.mssql.MSSQLNAdapter method), 21

execute() (pydal.adapters.mssql.VerticaAdapter method), 22

execute() (pydal.adapters.oracle.OracleAdapter method), 23

execute() (pydal.adapters.postgres.PostgreSQLAdapter method), 25

execute() (pydal.adapters.sqlite.JDBCSQLiteAdapter method), 26

execute_test_query() (pydal.adapters.base.BaseAdapter method), 6

execute_test_query() (pydal.adapters.base.NoSQLAdapter method), 8

executesql() (pydal.base.DAL method), 36

exists() (pydal.helpers.classes.DatabaseStoredFile static method), 28

expand() (pydal.adapters.base.BaseAdapter method), 6

expand() (pydal.adapters.couchdb.CouchDBAdapter method), 9

expand() (pydal.adapters.mongo.MongoDBAdapter method), 18

expand_all() (pydal.adapters.base.BaseAdapter method), 6

EXPAND_CASE() (pydal.adapters.mongo.MongoDBAdapter method), 16

export_to_csv_file() (pydal.base.DAL method), 37

export_to_csv_file() (pydal.objects.BasicRows method), 40

Expression (class in pydal.objects), 40

EXTRACT() (pydal.adapters.base.BaseAdapter method), 4

EXTRACT() (pydal.adapters.base.NoSQLAdapter method), 8

EXTRACT() (pydal.adapters.mongo.MongoDBAdapter method), 17

EXTRACT() (pydal.adapters.mssql.MSSQLAdapter method), 20

EXTRACT() (pydal.adapters.mssql.VerticaAdapter method), 22

EXTRACT() (pydal.adapters.sqlite.SQLiteAdapter method), 26

F

FakeCursor (class in pydal.helpers.classes), 28

FakeDriver (class in pydal.helpers.classes), 29

FALSE (pydal.adapters.base.BaseAdapter attribute), 4

FALSE (pydal.adapters.mssql.MSSQLAdapter attribute), 20

FALSE_exp (pydal.adapters.base.BaseAdapter attribute), 4

Field (class in pydal.objects), 42

FieldMethod (class in pydal.objects), 43

fields (pydal.base.DAL.Table attribute), 35

fields (pydal.objects.Table attribute), 46

FieldVirtual (class in pydal.objects), 43

file_close() (pydal.adapters.base.BaseAdapter method), 6

file_close() (pydal.adapters.couchdb.CouchDBAdapter method), 9

- file_close() (pydal.helpers.classes.UseDatabaseStoredFile method), 30
 - file_delete() (pydal.adapters.base.BaseAdapter method), 6
 - file_delete() (pydal.helpers.classes.UseDatabaseStoredFile method), 30
 - file_exists() (pydal.adapters.base.BaseAdapter method), 6
 - file_exists() (pydal.adapters.couchdb.CouchDBAdapter method), 9
 - file_exists() (pydal.helpers.classes.UseDatabaseStoredFile method), 30
 - file_open() (pydal.adapters.base.BaseAdapter method), 6
 - file_open() (pydal.adapters.couchdb.CouchDBAdapter method), 9
 - file_open() (pydal.helpers.classes.UseDatabaseStoredFile method), 30
 - find() (pydal.objects.Rows method), 44
 - find_driver() (pydal.adapters.base.BaseAdapter method), 6
 - find_or_make_work_folder() (pydal.connection.ConnectionPool method), 39
 - FireBirdAdapter (class in pydal.adapters.firebird), 10
 - FireBirdEmbeddedAdapter (class in pydal.adapters.firebird), 11
 - first() (pydal.objects.IterRows method), 43
 - first() (pydal.objects.Rows method), 45
 - folder (pydal.adapters.base.BaseAdapter attribute), 6
 - formatter() (pydal.objects.Field method), 42
- ## G
- GE() (pydal.adapters.base.BaseAdapter method), 4
 - GE() (pydal.adapters.imap.IMAPAdapter method), 13
 - GE() (pydal.adapters.mongo.MongoDBAdapter method), 17
 - geoLine() (in module pydal.helpers.methods), 30
 - geoPoint() (in module pydal.helpers.methods), 30
 - geoPolygon() (in module pydal.helpers.methods), 31
 - get() (pydal.helpers.classes.BasicStorage method), 28
 - get() (pydal.helpers.classes.Reference method), 29
 - get() (pydal.objects.Row method), 44
 - get_charset() (pydal.adapters.imap.IMAPAdapter method), 14
 - get_collection() (pydal.adapters.mongo.MongoDBAdapter method), 17
 - get_instances() (pydal.base.DAL static method), 37
 - get_last_message() (pydal.adapters.imap.IMAPAdapter method), 14
 - get_mailboxes() (pydal.adapters.imap.IMAPAdapter method), 14
 - get_query_mailbox() (pydal.adapters.imap.IMAPAdapter method), 14
 - get_table() (pydal.adapters.base.BaseAdapter method), 6
 - get_uid_bounds() (pydal.adapters.imap.IMAPAdapter method), 14
 - GoogleDatastoreAdapter (in module pydal.adapters), 28
 - group_by_value() (pydal.objects.Rows method), 45
 - GROUP_MARK (pydal.adapters.mongo.MongoDBAdapter attribute), 17
 - GT() (pydal.adapters.base.BaseAdapter method), 4
 - GT() (pydal.adapters.imap.IMAPAdapter method), 13
 - GT() (pydal.adapters.mongo.MongoDBAdapter method), 17
- ## H
- has_field() (pydal.adapters.mongo.MongoDBAdapter static method), 18
 - has_key() (pydal.helpers.classes.BasicStorage method), 28
 - has_representer() (pydal.base.DAL method), 37
 - header_represent() (pydal.adapters.imap.IMAPAdapter static method), 14
 - hide_password() (in module pydal.helpers.methods), 31
 - hour() (pydal.objects.Expression method), 41
- ## I
- id_query() (pydal.adapters.base.BaseAdapter method), 6
 - id_query() (pydal.adapters.base.NoSQLAdapter method), 8
 - ILIKE() (pydal.adapters.base.BaseAdapter method), 4
 - ILIKE() (pydal.adapters.base.NoSQLAdapter method), 8
 - ILIKE() (pydal.adapters.mongo.MongoDBAdapter method), 17
 - ILIKE() (pydal.adapters.mssql.MSSQL2Adapter method), 18
 - ILIKE() (pydal.adapters.mssql.MSSQLAdapter method), 20
 - ILIKE() (pydal.adapters.mssql.MSSQLNAdapter method), 21
 - ILIKE() (pydal.adapters.postgres.NewPostgreSQLAdapter method), 24
 - ILIKE() (pydal.adapters.postgres.PostgreSQLAdapter method), 24
 - ilike() (pydal.objects.Expression method), 41
 - IMAPAdapter (class in pydal.adapters.imap), 11
 - import_from_csv_file() (pydal.base.DAL method), 37
 - import_from_csv_file() (pydal.base.DAL.Table method), 35
 - import_from_csv_file() (pydal.objects.Table method), 46
 - import_table_definitions() (pydal.base.DAL method), 37
 - InformixAdapter (class in pydal.adapters.informix), 15
 - InformixSEAdapter (class in pydal.adapters.informix), 15
 - IngresAdapter (class in pydal.adapters.ingres), 15
 - IngresUnicodeAdapter (class in pydal.adapters.ingres), 16
 - insert() (pydal.adapters.base.BaseAdapter method), 6

- insert() (pydal.adapters.couchdb.CouchDBAdapter method), 9
- insert() (pydal.adapters.imap.IMAPAdapter method), 14
- insert() (pydal.adapters.mongo.MongoDBAdapter method), 18
- insert() (pydal.base.DAL.Table method), 36
- insert() (pydal.objects.Table method), 46
- int2uuid() (in module pydal.helpers.methods), 31
- INVERT() (pydal.adapters.base.BaseAdapter method), 4
- INVERT() (pydal.adapters.mongo.MongoDBAdapter method), 17
- is_flag() (pydal.adapters.imap.IMAPAdapter method), 14
- is_numerical_type() (pydal.adapters.base.BaseAdapter method), 6
- isempty() (pydal.objects.LazySet method), 43
- isempty() (pydal.objects.Set method), 46
- isOperationalError() (pydal.adapters.base.BaseAdapter method), 6
- isProgrammingError() (pydal.adapters.base.BaseAdapter method), 6
- items() (pydal.helpers.classes.BasicStorage method), 28
- iteritems() (pydal.helpers.classes.BasicStorage method), 28
- iterkeys() (pydal.helpers.classes.BasicStorage method), 28
- iterparse() (pydal.adapters.base.BaseAdapter method), 6
- IterRows (class in pydal.objects), 43
- iterselect() (pydal.adapters.base.BaseAdapter method), 6
- iterselect() (pydal.objects.Set method), 46
- itervalues() (pydal.helpers.classes.BasicStorage method), 28
- ## J
- JDBCPostgreSQLAdapter (class in pydal.adapters.postgres), 24
- JDBCSQLiteAdapter (class in pydal.adapters.sqlite), 26
- JOIN() (pydal.adapters.base.BaseAdapter method), 4
- json() (pydal.objects.BasicRows method), 40
- ## K
- keys() (pydal.helpers.classes.BasicStorage method), 28
- ## L
- last() (pydal.objects.Rows method), 45
- lastrowid (pydal.helpers.classes.NullCursor attribute), 29
- lastrowid() (pydal.adapters.base.BaseAdapter method), 6
- lastrowid() (pydal.adapters.base.NoSQLAdapter method), 8
- lastrowid() (pydal.adapters.db2.DB2Adapter method), 10
- lastrowid() (pydal.adapters.firebird.FireBirdAdapter method), 11
- lastrowid() (pydal.adapters.informix.InformixAdapter method), 15
- lastrowid() (pydal.adapters.ingres.IngresAdapter method), 15
- lastrowid() (pydal.adapters.mssql.MSSQLAdapter method), 21
- lastrowid() (pydal.adapters.mssql.VerticaAdapter method), 22
- lastrowid() (pydal.adapters.oracle.OracleAdapter method), 23
- lastrowid() (pydal.adapters.postgres.PostgreSQLAdapter method), 25
- lastrowid() (pydal.adapters.sapdb.SAPDBAdapter method), 26
- Lazy (pydal.objects.Field attribute), 42
- lazy_define_table() (pydal.base.DAL method), 37
- LazyReferenceGetter (class in pydal.objects), 43
- LazySet (class in pydal.objects), 43
- LE() (pydal.adapters.base.BaseAdapter method), 4
- LE() (pydal.adapters.imap.IMAPAdapter method), 13
- LE() (pydal.adapters.mongo.MongoDBAdapter method), 17
- LEFT_JOIN() (pydal.adapters.base.BaseAdapter method), 4
- LEFT_JOIN() (pydal.adapters.base.NoSQLAdapter method), 8
- LEFT_JOIN() (pydal.adapters.db2.DB2Adapter method), 10
- LEFT_JOIN() (pydal.adapters.ingres.IngresAdapter method), 15
- LEFT_JOIN() (pydal.adapters.mssql.MSSQLAdapter method), 20
- LEFT_JOIN() (pydal.adapters.oracle.OracleAdapter method), 23
- LEFT_JOIN() (pydal.adapters.teradata.TeradataAdapter method), 27
- len() (pydal.objects.Expression method), 41
- LENGTH() (pydal.adapters.base.BaseAdapter method), 4
- LENGTH() (pydal.adapters.base.NoSQLAdapter method), 8
- LENGTH() (pydal.adapters.firebird.FireBirdAdapter method), 10
- LENGTH() (pydal.adapters.mongo.MongoDBAdapter method), 17
- LENGTH() (pydal.adapters.mssql.MSSQLAdapter method), 20
- LIKE() (pydal.adapters.base.BaseAdapter method), 4
- LIKE() (pydal.adapters.mongo.MongoDBAdapter method), 17
- LIKE() (pydal.adapters.mssql.MSSQLAdapter method), 20
- LIKE() (pydal.adapters.postgres.PostgreSQLAdapter method), 24
- like() (pydal.objects.Expression method), 41
- like_escaper_default() (pydal.adapters.base.BaseAdapter method), 6

- like_escaper_default() (pydal.adapters.mssql.MSSQLAdapter method), 21
 - list_represent() (in module pydal.helpers.methods), 31
 - log() (pydal.adapters.base.BaseAdapter method), 6
 - log_execute() (pydal.adapters.base.BaseAdapter method), 6
 - log_execute() (pydal.adapters.base.NoSQLAdapter method), 8
 - logger (pydal.base.DAL attribute), 37
 - LOWER() (pydal.adapters.base.BaseAdapter method), 4
 - LOWER() (pydal.adapters.base.NoSQLAdapter method), 8
 - LOWER() (pydal.adapters.mongo.MongoDBAdapter method), 17
 - lower() (pydal.objects.Expression method), 41
 - LT() (pydal.adapters.base.BaseAdapter method), 4
 - LT() (pydal.adapters.imap.IMAPAdapter method), 13
 - LT() (pydal.adapters.mongo.MongoDBAdapter method), 17
- ## M
- max() (pydal.objects.Expression method), 41
 - MetaDAL (class in pydal.base), 38
 - Method (pydal.objects.Field attribute), 42
 - MethodAdder (class in pydal.helpers.classes), 29
 - migrate_table() (pydal.adapters.base.BaseAdapter method), 6
 - migrate_table() (pydal.adapters.base.NoSQLAdapter method), 8
 - min() (pydal.objects.Expression method), 41
 - minutes() (pydal.objects.Expression method), 41
 - MOD() (pydal.adapters.base.BaseAdapter method), 4
 - MOD() (pydal.adapters.mongo.MongoDBAdapter method), 17
 - MONGO_BLOB_BYTES (pydal.adapters.mongo.MongoBlob attribute), 16
 - MONGO_BLOB_NON_UTF8_STR (pydal.adapters.mongo.MongoBlob attribute), 16
 - MongoBlob (class in pydal.adapters.mongo), 16
 - MongoDBAdapter (class in pydal.adapters.mongo), 16
 - MongoDBAdapter.Expanded (class in pydal.adapters.mongo), 17
 - MongoDBAdapter.NotOnNoSqlError, 17
 - month() (pydal.objects.Expression method), 41
 - MSSQL2Adapter (class in pydal.adapters.mssql), 18
 - MSSQL3Adapter (class in pydal.adapters.mssql), 19
 - MSSQL3NAdapter (class in pydal.adapters.mssql), 19
 - MSSQL4Adapter (class in pydal.adapters.mssql), 19
 - MSSQL4NAdapter (class in pydal.adapters.mssql), 19
 - mssql_like_normalizer() (pydal.adapters.mssql.MSSQLAdapter method), 21
 - MSSQLAdapter (class in pydal.adapters.mssql), 20
 - MSSQLNAdapter (class in pydal.adapters.mssql), 21
 - MUL() (pydal.adapters.base.BaseAdapter method), 4
 - MUL() (pydal.adapters.base.NoSQLAdapter method), 8
 - MUL() (pydal.adapters.mongo.MongoDBAdapter method), 17
 - MySQLAdapter (class in pydal.adapters.mysql), 22
- ## N
- NE() (pydal.adapters.base.BaseAdapter method), 4
 - NE() (pydal.adapters.couchdb.CouchDBAdapter method), 9
 - NE() (pydal.adapters.imap.IMAPAdapter method), 13
 - NE() (pydal.adapters.mongo.MongoDBAdapter method), 17
 - needs_mongodb_aggregation_pipeline() (pydal.adapters.mongo.MongoDBAdapter method), 18
 - nested_select() (pydal.objects.LazySet method), 43
 - nested_select() (pydal.objects.Set method), 46
 - NewPostgreSQLAdapter (class in pydal.adapters.postgres), 24
 - next() (pydal.objects.IterRows method), 43
 - NoSQLAdapter (class in pydal.adapters.base), 7
 - NOT() (pydal.adapters.base.BaseAdapter method), 4
 - NOT() (pydal.adapters.imap.IMAPAdapter method), 13
 - NOT() (pydal.adapters.mongo.MongoDBAdapter method), 17
 - NOT_NULL() (pydal.adapters.base.BaseAdapter method), 4
 - NOT_NULL() (pydal.adapters.firebird.FireBirdAdapter method), 10
 - NOT_NULL() (pydal.adapters.informix.InformixAdapter method), 15
 - NOT_NULL() (pydal.adapters.oracle.OracleAdapter method), 23
 - NullCursor (class in pydal.helpers.classes), 29
 - NullDriver (class in pydal.helpers.classes), 29
- ## O
- object_id() (pydal.adapters.mongo.MongoDBAdapter method), 18
 - ON() (pydal.adapters.base.BaseAdapter method), 4
 - ON() (pydal.adapters.base.NoSQLAdapter method), 8
 - ON() (pydal.adapters.mongo.MongoDBAdapter method), 17
 - on() (pydal.base.DAL.Table method), 36
 - on() (pydal.objects.Table method), 46
 - OR() (pydal.adapters.base.BaseAdapter method), 4
 - OR() (pydal.adapters.base.NoSQLAdapter method), 8
 - OR() (pydal.adapters.couchdb.CouchDBAdapter method), 9
 - OR() (pydal.adapters.imap.IMAPAdapter method), 14

- OR() (pydal.adapters.mongo.MongoDBAdapter method), 17
- oracle_fix (pydal.adapters.oracle.OracleAdapter attribute), 23
- OracleAdapter (class in pydal.adapters.oracle), 23
- ## P
- parse() (pydal.adapters.base.BaseAdapter method), 6
- parse() (pydal.objects.Set method), 46
- parse_as_rest() (pydal.base.DAL method), 37
- parse_blob() (pydal.adapters.base.BaseAdapter method), 6
- parse_blob() (pydal.adapters.mongo.MongoDBAdapter method), 18
- parse_boolean() (pydal.adapters.base.BaseAdapter method), 6
- parse_data() (pydal.adapters.mongo.MongoDBAdapter static method), 18
- parse_date() (pydal.adapters.base.BaseAdapter method), 6
- parse_datetime() (pydal.adapters.base.BaseAdapter method), 6
- parse_decimal() (pydal.adapters.base.BaseAdapter method), 6
- parse_double() (pydal.adapters.base.BaseAdapter method), 6
- parse_id() (pydal.adapters.base.BaseAdapter method), 6
- parse_id() (pydal.adapters.mongo.MongoDBAdapter method), 18
- parse_integer() (pydal.adapters.base.BaseAdapter method), 6
- parse_json() (pydal.adapters.base.BaseAdapter method), 6
- parse_list_integers() (pydal.adapters.base.BaseAdapter method), 6
- parse_list_integers() (pydal.adapters.base.NoSQLAdapter method), 9
- parse_list_integers() (pydal.adapters.postgres.NewPostgreSQLAdapter method), 24
- parse_list_references() (pydal.adapters.base.BaseAdapter method), 6
- parse_list_references() (pydal.adapters.base.NoSQLAdapter method), 9
- parse_list_references() (pydal.adapters.postgres.NewPostgreSQLAdapter method), 24
- parse_list_strings() (pydal.adapters.base.BaseAdapter method), 7
- parse_list_strings() (pydal.adapters.base.NoSQLAdapter method), 9
- parse_list_strings() (pydal.adapters.postgres.NewPostgreSQLAdapter method), 24
- parse_reference() (pydal.adapters.base.BaseAdapter method), 7
- parse_reference() (pydal.adapters.mongo.MongoDBAdapter method), 18
- parse_time() (pydal.adapters.base.BaseAdapter method), 7
- parse_value() (pydal.adapters.base.BaseAdapter method), 7
- pickle_basicstorage() (in module pydal.helpers.classes), 30
- pickle_row() (in module pydal.objects), 47
- pluralize() (in module pydal.helpers.methods), 31
- POOLS (pydal.connection.ConnectionPool attribute), 39
- pop() (pydal.helpers.classes.BasicStorage method), 28
- PostgreSQLAdapter (class in pydal.adapters.postgres), 24
- prepare() (pydal.adapters.base.BaseAdapter method), 7
- prepare() (pydal.adapters.base.NoSQLAdapter method), 9
- prepare() (pydal.adapters.mysql.MySQLAdapter method), 23
- prepare() (pydal.adapters.postgres.PostgreSQLAdapter method), 25
- PRIMARY_KEY() (pydal.adapters.base.BaseAdapter method), 4
- PRIMARY_KEY() (pydal.adapters.base.NoSQLAdapter method), 8
- PRIMARY_KEY() (pydal.adapters.mssql.MSSQLAdapter method), 20
- pydal (module), 47
- pydal.adapters (module), 28
- pydal.adapters.base (module), 3
- pydal.adapters.couchdb (module), 9
- pydal.adapters.cubrid (module), 10
- pydal.adapters.db2 (module), 10
- pydal.adapters.firebird (module), 10
- pydal.adapters.imap (module), 11
- pydal.adapters.informix (module), 15
- pydal.adapters.ingres (module), 15
- pydal.adapters.mongo (module), 16
- pydal.adapters.mssql (module), 18
- pydal.adapters.mysql (module), 22
- pydal.adapters.oracle (module), 23
- pydal.adapters.postgres (module), 24
- pydal.adapters.sapdb (module), 26
- pydal.adapters.sqlite (module), 26
- pydal.adapters.teradata (module), 27
- pydal.base (module), 31
- pydal.connection (module), 39
- pydal.helpers (module), 31
- pydal.helpers.classes (module), 28

pydal.helpers.methods (module), 30
 pydal.helpers.regex (module), 31
 pydal.objects (module), 39

Q

Query (class in pydal.objects), 43
 QUOTE_TEMPLATE (pydal.adapters.base.BaseAdapter attribute), 4
 QUOTE_TEMPLATE (pydal.adapters.base.NoSQLAdapter attribute), 8
 QUOTE_TEMPLATE (pydal.adapters.mssql.MSSQLAdapter attribute), 20
 QUOTE_TEMPLATE (pydal.adapters.mysql.MySQLAdapter attribute), 22
 QUOTE_TEMPLATE (pydal.adapters.postgres.PostgreSQLAdapter attribute), 24

R

RANDOM() (pydal.adapters.base.BaseAdapter method), 4
 RANDOM() (pydal.adapters.base.NoSQLAdapter method), 8
 RANDOM() (pydal.adapters.db2.DB2Adapter method), 10
 RANDOM() (pydal.adapters.firebird.FireBirdAdapter method), 11
 RANDOM() (pydal.adapters.informix.InformixAdapter method), 15
 RANDOM() (pydal.adapters.ingres.IngresAdapter method), 15
 RANDOM() (pydal.adapters.mongo.MongoDBAdapter method), 17
 RANDOM() (pydal.adapters.mssql.MSSQLAdapter method), 20
 RANDOM() (pydal.adapters.mysql.MySQLAdapter method), 22
 RANDOM() (pydal.adapters.oracle.OracleAdapter method), 23
 RANDOM() (pydal.adapters.postgres.PostgreSQLAdapter method), 24
 RAW() (pydal.adapters.base.BaseAdapter method), 4
 read() (pydal.helpers.classes.DatabaseStoredFile method), 28
 readline() (pydal.helpers.classes.DatabaseStoredFile method), 28
 reconnect() (pydal.adapters.imap.IMAPAdapter method), 14
 reconnect() (pydal.connection.ConnectionPool method), 39
 RecordDeleter (class in pydal.helpers.classes), 29

RecordUpdater (class in pydal.helpers.classes), 29
 Reference (class in pydal.helpers.classes), 29
 Reference_pickler() (in module pydal.helpers.classes), 29
 Reference_unpickler() (in module pydal.helpers.classes), 29
 REGEX_ARGPATTERN (pydal.adapters.mssql.MSSQLAdapter attribute), 20
 REGEX_DSN (pydal.adapters.mssql.MSSQLAdapter attribute), 20
 REGEX_SELECT_AS_PARSER (pydal.adapters.mongo.MongoDBAdapter attribute), 17
 REGEX_URI (pydal.adapters.cubrid.CubridAdapter attribute), 10
 REGEX_URI (pydal.adapters.firebird.FireBirdAdapter attribute), 11
 REGEX_URI (pydal.adapters.firebird.FireBirdEmbeddedAdapter attribute), 11
 REGEX_URI (pydal.adapters.imap.IMAPAdapter attribute), 14
 REGEX_URI (pydal.adapters.informix.InformixAdapter attribute), 15
 REGEX_URI (pydal.adapters.mssql.MSSQLAdapter attribute), 20
 REGEX_URI (pydal.adapters.mysql.MySQLAdapter attribute), 22
 REGEX_URI (pydal.adapters.postgres.JDBCPostgreSQLAdapter attribute), 24
 REGEX_URI (pydal.adapters.postgres.PostgreSQLAdapter attribute), 25
 REGEX_URI (pydal.adapters.sapdb.SAPDBAdapter attribute), 26
 REGEXP() (pydal.adapters.base.BaseAdapter method), 4
 REGEXP() (pydal.adapters.mongo.MongoDBAdapter method), 17
 REGEXP() (pydal.adapters.mssql.MSSQLAdapter method), 20
 REGEXP() (pydal.adapters.mysql.MySQLAdapter method), 22
 REGEXP() (pydal.adapters.oracle.OracleAdapter method), 23
 REGEXP() (pydal.adapters.postgres.PostgreSQLAdapter method), 24
 REGEXP() (pydal.adapters.sqlite.SQLiteAdapter method), 26
 regexp() (pydal.objects.Expression method), 41
 REGEXP_MARK1 (pydal.adapters.mongo.MongoDBAdapter attribute), 17
 REGEXP_MARK2 (pydal.adapters.mongo.MongoDBAdapter attribute), 17
 register() (pydal.helpers.classes.MethodAdder method),

- 29
- render() (pydal.objects.Rows method), 45
- REPLACE() (pydal.adapters.base.BaseAdapter method), 5
- replace() (pydal.objects.Expression method), 41
- represent() (pydal.adapters.base.BaseAdapter method), 7
- represent() (pydal.adapters.base.NoSQLAdapter method), 9
- represent() (pydal.adapters.couchdb.CouchDBAdapter method), 9
- represent() (pydal.adapters.mongo.MongoDBAdapter method), 18
- represent() (pydal.adapters.mssql.MSSQL2Adapter method), 19
- represent() (pydal.adapters.mssql.MSSQLAdapter method), 21
- represent() (pydal.adapters.mssql.MSSQLNAdapter method), 21
- represent() (pydal.adapters.postgres.NewPostgreSQLAdapter method), 24
- represent() (pydal.adapters.postgres.PostgreSQLAdapter method), 25
- represent() (pydal.adapters.sqlite.SpatialiteAdapter method), 27
- represent() (pydal.base.DAL method), 38
- represent_exceptions() (pydal.adapters.base.BaseAdapter method), 7
- represent_exceptions() (pydal.adapters.base.NoSQLAdapter method), 9
- represent_exceptions() (pydal.adapters.db2.DB2Adapter method), 10
- represent_exceptions() (pydal.adapters.informix.InformixAdapter method), 15
- represent_exceptions() (pydal.adapters.oracle.OracleAdapter method), 23
- representers (pydal.base.DAL attribute), 38
- retrieve() (pydal.objects.Field method), 43
- retrieve_file_properties() (pydal.objects.Field method), 43
- rollback() (pydal.adapters.base.BaseAdapter method), 7
- rollback() (pydal.adapters.base.NoSQLAdapter method), 9
- rollback() (pydal.base.DAL method), 38
- rollback_prepared() (pydal.adapters.base.BaseAdapter method), 7
- rollback_prepared() (pydal.adapters.base.NoSQLAdapter method), 9
- rollback_prepared() (pydal.adapters.mysql.MySQLAdapter method), 23
- rollback_prepared() (pydal.adapters.postgres.PostgreSQLAdapter method), 25
- Row (class in pydal.objects), 44
- Rows (class in pydal.objects), 44
- rowslice() (pydal.adapters.base.BaseAdapter method), 7
- rowslice() (pydal.adapters.base.NoSQLAdapter method), 9
- rowslice() (pydal.adapters.db2.DB2Adapter method), 10
- rowslice() (pydal.adapters.informix.InformixSEAdapter method), 15
- rowslice() (pydal.adapters.mssql.MSSQL3Adapter method), 19
- rowslice() (pydal.adapters.mssql.MSSQL3NAdapter method), 19
- rowslice() (pydal.adapters.mssql.MSSQL4Adapter method), 19
- rowslice() (pydal.adapters.mssql.MSSQL4NAdapter method), 20
- rowslice() (pydal.adapters.mssql.MSSQLAdapter method), 21
- ## S
- SAPDBAdapter (class in pydal.adapters.sapdb), 26
- save_dbt() (pydal.adapters.base.BaseAdapter method), 7
- seconds() (pydal.objects.Expression method), 41
- select() (pydal.adapters.base.BaseAdapter method), 7
- select() (pydal.adapters.couchdb.CouchDBAdapter method), 9
- select() (pydal.adapters.imap.IMAPAdapter method), 14
- select() (pydal.adapters.mongo.MongoDBAdapter method), 18
- select() (pydal.adapters.sqlite.SQLiteAdapter method), 27
- select() (pydal.objects.LazySet method), 43
- select() (pydal.objects.Set method), 46
- select_limitby() (pydal.adapters.base.BaseAdapter method), 7
- select_limitby() (pydal.adapters.db2.DB2Adapter method), 10
- select_limitby() (pydal.adapters.firebird.FireBirdAdapter method), 11
- select_limitby() (pydal.adapters.informix.InformixAdapter method), 15
- select_limitby() (pydal.adapters.informix.InformixSEAdapter method), 15
- select_limitby() (pydal.adapters.ingres.IngresAdapter method), 15
- select_limitby() (pydal.adapters.mssql.MSSQL3Adapter method), 19
- select_limitby() (pydal.adapters.mssql.MSSQL3NAdapter method), 19
- select_limitby() (pydal.adapters.mssql.MSSQL4Adapter method), 19

select_limitby() (pydal.adapters.mssql.MSSQL4NAdapter method), 20
 select_limitby() (pydal.adapters.mssql.MSSQLAdapter method), 21
 select_limitby() (pydal.adapters.mssql.VerticaAdapter method), 22
 select_limitby() (pydal.adapters.oracle.OracleAdapter method), 23
 select_limitby() (pydal.adapters.sapdb.SAPDBAdapter method), 26
 select_limitby() (pydal.adapters.teradata.TeradataAdapter method), 27
 sequence_name() (pydal.adapters.base.BaseAdapter method), 7
 sequence_name() (pydal.adapters.firebird.FireBirdAdapter method), 11
 sequence_name() (pydal.adapters.postgres.PostgreSQLAdapter method), 25
 sequence_name() (pydal.adapters.sapdb.SAPDBAdapter method), 26
 Serializable (class in pydal.helpers.classes), 30
 serializers (pydal.base.DAL attribute), 38
 Set (class in pydal.objects), 45
 set_attributes() (pydal.objects.Field method), 43
 set_folder() (pydal.base.DAL static method), 38
 set_folder() (pydal.connection.ConnectionPool static method), 39
 setvirtualfields() (pydal.objects.Rows method), 45
 smart_adapt() (pydal.adapters.base.BaseAdapter method), 7
 smart_query() (in module pydal.helpers.methods), 31
 smart_query() (pydal.base.DAL method), 38
 sort() (pydal.objects.Rows method), 45
 SpatiaLiteAdapter (class in pydal.adapters.sqlite), 27
 SQLALL (class in pydal.helpers.classes), 29
 SQLCallableList (class in pydal.helpers.classes), 29
 SQLCustomType (class in pydal.helpers.classes), 29
 SQLiteAdapter (class in pydal.adapters.sqlite), 26
 sqlsafe (pydal.base.DAL.Table attribute), 36
 sqlsafe (pydal.objects.Field attribute), 43
 sqlsafe (pydal.objects.Table attribute), 46
 sqlsafe_alias (pydal.base.DAL.Table attribute), 36
 sqlsafe_alias (pydal.objects.Table attribute), 47
 sqlsafe_field() (pydal.adapters.base.BaseAdapter method), 7
 sqlsafe_name (pydal.objects.Field attribute), 43
 sqlsafe_table() (pydal.adapters.base.BaseAdapter method), 7
 sqlsafe_table() (pydal.adapters.oracle.OracleAdapter method), 23
 ST_AS GEOJSON() (pydal.adapters.postgres.PostgreSQLAdapter method), 25
 ST_AS GEOJSON() (pydal.adapters.sqlite.SpatiaLiteAdapter method), 27
 st_asgeojson() (pydal.objects.Expression method), 41
 ST_ASTEXT() (pydal.adapters.mssql.MSSQLAdapter method), 21
 ST_ASTEXT() (pydal.adapters.postgres.PostgreSQLAdapter method), 25
 ST_ASTEXT() (pydal.adapters.sqlite.SpatiaLiteAdapter method), 27
 st_astext() (pydal.objects.Expression method), 41
 ST_CONTAINS() (pydal.adapters.mssql.MSSQLAdapter method), 21
 ST_CONTAINS() (pydal.adapters.postgres.PostgreSQLAdapter method), 25
 ST_CONTAINS() (pydal.adapters.sqlite.SpatiaLiteAdapter method), 27
 st_contains() (pydal.objects.Expression method), 41
 ST_DISTANCE() (pydal.adapters.mssql.MSSQLAdapter method), 21
 ST_DISTANCE() (pydal.adapters.postgres.PostgreSQLAdapter method), 25
 ST_DISTANCE() (pydal.adapters.sqlite.SpatiaLiteAdapter method), 27
 st_distance() (pydal.objects.Expression method), 41
 ST_DWITHIN() (pydal.adapters.postgres.PostgreSQLAdapter method), 25
 st_dwithin() (pydal.objects.Expression method), 41
 ST_EQUALS() (pydal.adapters.mssql.MSSQLAdapter method), 21
 ST_EQUALS() (pydal.adapters.postgres.PostgreSQLAdapter method), 25
 ST_EQUALS() (pydal.adapters.sqlite.SpatiaLiteAdapter method), 27
 st_equals() (pydal.objects.Expression method), 41
 ST_INTERSECTS() (pydal.adapters.mssql.MSSQLAdapter method), 21
 ST_INTERSECTS() (pydal.adapters.postgres.PostgreSQLAdapter method), 25
 ST_INTERSECTS() (pydal.adapters.sqlite.SpatiaLiteAdapter method), 27
 st_intersects() (pydal.objects.Expression method), 41
 ST_OVERLAPS() (pydal.adapters.mssql.MSSQLAdapter method), 21
 ST_OVERLAPS() (pydal.adapters.postgres.PostgreSQLAdapter method), 25
 ST_OVERLAPS() (pydal.adapters.sqlite.SpatiaLiteAdapter method), 27
 st_overlaps() (pydal.objects.Expression method), 41

- ST_SIMPLIFY() (pydal.adapters.postgres.PostgreSQLAdapter method), 25
- ST_SIMPLIFY() (pydal.adapters.sqlite.SpatialLiteAdapter method), 27
- st_simplify() (pydal.objects.Expression method), 41
- ST_SIMPLIFYPRESERVETOPOLOGY() (pydal.adapters.postgres.PostgreSQLAdapter method), 25
- st_simplifypreservetopology() (pydal.objects.Expression method), 41
- ST_TOUCHES() (pydal.adapters.mssql.MSSQLAdapter method), 21
- ST_TOUCHES() (pydal.adapters.postgres.PostgreSQLAdapter method), 25
- ST_TOUCHES() (pydal.adapters.sqlite.SpatialLiteAdapter method), 27
- st_touches() (pydal.objects.Expression method), 41
- ST_WITHIN() (pydal.adapters.mssql.MSSQLAdapter method), 21
- ST_WITHIN() (pydal.adapters.postgres.PostgreSQLAdapter method), 25
- ST_WITHIN() (pydal.adapters.sqlite.SpatialLiteAdapter method), 27
- st_within() (pydal.objects.Expression method), 41
- ST_X() (pydal.adapters.postgres.PostgreSQLAdapter method), 25
- st_x() (pydal.objects.Expression method), 41
- ST_Y() (pydal.adapters.postgres.PostgreSQLAdapter method), 25
- st_y() (pydal.objects.Expression method), 41
- STARTSWITH() (pydal.adapters.base.BaseAdapter method), 5
- STARTSWITH() (pydal.adapters.base.NoSQLAdapter method), 8
- STARTSWITH() (pydal.adapters.mongo.MongoDBAdapter method), 17
- STARTSWITH() (pydal.adapters.mssql.MSSQLAdapter method), 20
- startswith() (pydal.helpers.classes.SQLCustomType method), 30
- startswith() (pydal.objects.Expression method), 41
- store() (pydal.objects.Field method), 43
- SUB() (pydal.adapters.base.BaseAdapter method), 5
- SUB() (pydal.adapters.base.NoSQLAdapter method), 8
- SUB() (pydal.adapters.mongo.MongoDBAdapter method), 17
- SUBSTRING() (pydal.adapters.base.BaseAdapter method), 5
- SUBSTRING() (pydal.adapters.base.NoSQLAdapter method), 8
- SUBSTRING() (pydal.adapters.firebird.FireBirdAdapter method), 11
- SUBSTRING() (pydal.adapters.mongo.MongoDBAdapter method), 17
- SUBSTRING() (pydal.adapters.mssql.MSSQLAdapter method), 21
- SUBSTRING() (pydal.adapters.mysql.MySQLAdapter method), 22
- sum() (pydal.objects.Expression method), 41
- support_distributed_transaction (pydal.adapters.base.BaseAdapter attribute), 7
- support_distributed_transaction (pydal.adapters.firebird.FireBirdAdapter attribute), 11
- support_distributed_transaction (pydal.adapters.mysql.MySQLAdapter attribute), 23
- support_distributed_transaction (pydal.adapters.postgres.PostgreSQLAdapter attribute), 26
- support_distributed_transaction (pydal.adapters.sapdb.SAPDBAdapter attribute), 26
- SybaseAdapter (class in pydal.adapters.mssql), 21
- ## T
- T_SEP (pydal.adapters.base.BaseAdapter attribute), 5
- T_SEP (pydal.adapters.mssql.MSSQLAdapter attribute), 21
- T_SEP (pydal.adapters.mssql.VerticaAdapter attribute), 22
- Table (class in pydal.objects), 46
- table_alias() (pydal.adapters.base.BaseAdapter method), 7
- tables (pydal.base.DAL attribute), 38
- tables() (pydal.adapters.base.BaseAdapter method), 7
- TeradataAdapter (class in pydal.adapters.teradata), 27
- test_query (pydal.adapters.base.BaseAdapter attribute), 7
- trigger_name() (pydal.adapters.base.BaseAdapter method), 7
- trigger_name() (pydal.adapters.firebird.FireBirdAdapter method), 11
- trigger_name() (pydal.adapters.oracle.OracleAdapter method), 23
- TRUE (pydal.adapters.base.BaseAdapter attribute), 5
- TRUE (pydal.adapters.mssql.MSSQLAdapter attribute), 21
- TRUE_exp (pydal.adapters.base.BaseAdapter attribute), 5
- truncate() (pydal.adapters.base.BaseAdapter method), 7
- truncate() (pydal.adapters.mongo.MongoDBAdapter method), 18
- truncate() (pydal.base.DAL.Table method), 36
- truncate() (pydal.objects.Table method), 47
- try_create_web2py_filesystem() (pydal.helpers.classes.DatabaseStoredFile static method), 28

- try_json() (pydal.adapters.postgres.PostgreSQLAdapter method), 26
 - types (pydal.adapters.base.BaseAdapter attribute), 7
 - types (pydal.adapters.couchdb.CouchDBAdapter attribute), 9
 - types (pydal.adapters.db2.DB2Adapter attribute), 10
 - types (pydal.adapters.firebird.FireBirdAdapter attribute), 11
 - types (pydal.adapters.imap.IMAPAdapter attribute), 14
 - types (pydal.adapters.informix.InformixAdapter attribute), 15
 - types (pydal.adapters.ingres.IngresAdapter attribute), 15
 - types (pydal.adapters.ingres.IngresUnicodeAdapter attribute), 16
 - types (pydal.adapters.mongo.MongoDBAdapter attribute), 18
 - types (pydal.adapters.mssql.MSSQL2Adapter attribute), 19
 - types (pydal.adapters.mssql.MSSQL3Adapter attribute), 19
 - types (pydal.adapters.mssql.MSSQL3NAdapter attribute), 19
 - types (pydal.adapters.mssql.MSSQL4Adapter attribute), 19
 - types (pydal.adapters.mssql.MSSQL4NAdapter attribute), 20
 - types (pydal.adapters.mssql.MSSQLAdapter attribute), 21
 - types (pydal.adapters.mssql.MSSQLNAdapter attribute), 21
 - types (pydal.adapters.mssql.SybaseAdapter attribute), 22
 - types (pydal.adapters.mssql.VerticaAdapter attribute), 22
 - types (pydal.adapters.mysql.MySQLAdapter attribute), 23
 - types (pydal.adapters.oracle.OracleAdapter attribute), 23
 - types (pydal.adapters.postgres.NewPostgreSQLAdapter attribute), 24
 - types (pydal.adapters.postgres.PostgreSQLAdapter attribute), 26
 - types (pydal.adapters.sapdb.SAPDBAdapter attribute), 26
 - types (pydal.adapters.sqlite.SpatialLiteAdapter attribute), 27
 - types (pydal.adapters.teradata.TeradataAdapter attribute), 28
- U**
- update() (pydal.adapters.base.BaseAdapter method), 7
 - update() (pydal.adapters.couchdb.CouchDBAdapter method), 9
 - update() (pydal.adapters.imap.IMAPAdapter method), 14
 - update() (pydal.adapters.mongo.MongoDBAdapter method), 18
 - update() (pydal.base.DAL.Table method), 36
 - update() (pydal.helpers.classes.BasicStorage method), 28
 - update() (pydal.objects.LazySet method), 43
 - update() (pydal.objects.Set method), 46
 - update() (pydal.objects.Table method), 47
 - update_naive() (pydal.objects.LazySet method), 43
 - update_naive() (pydal.objects.Set method), 46
 - update_or_insert() (pydal.base.DAL.Table method), 36
 - update_or_insert() (pydal.objects.Table method), 47
 - uploads_in_blob (pydal.adapters.base.BaseAdapter attribute), 7
 - uploads_in_blob (pydal.adapters.couchdb.CouchDBAdapter attribute), 9
 - uploads_in_blob (pydal.adapters.mongo.MongoDBAdapter attribute), 18
 - UPPER() (pydal.adapters.base.BaseAdapter method), 5
 - UPPER() (pydal.adapters.base.NoSQLAdapter method), 8
 - UPPER() (pydal.adapters.mongo.MongoDBAdapter method), 18
 - upper() (pydal.objects.Expression method), 42
 - uri (pydal.adapters.imap.IMAPAdapter attribute), 14
 - use_common_filters() (in module pydal.helpers.methods), 31
 - UseDatabaseStoredFile (class in pydal.helpers.classes), 30
 - uuid() (pydal.base.DAL method), 38
 - uuid2int() (in module pydal.helpers.methods), 31
- V**
- validate() (pydal.objects.Field method), 43
 - validate_and_insert() (pydal.base.DAL.Table method), 36
 - validate_and_insert() (pydal.objects.Table method), 47
 - validate_and_update() (pydal.base.DAL.Table method), 36
 - validate_and_update() (pydal.objects.LazySet method), 43
 - validate_and_update() (pydal.objects.Set method), 46
 - validate_and_update() (pydal.objects.Table method), 47
 - validate_and_update_or_insert() (pydal.base.DAL.Table method), 36
 - validate_and_update_or_insert() (pydal.objects.Table method), 47
 - validate_second() (pydal.adapters.mongo.MongoDBAdapter method), 18
 - validators (pydal.base.DAL attribute), 38
 - validators_method (pydal.base.DAL attribute), 38
 - values() (pydal.helpers.classes.BasicStorage method), 28
 - varquote() (pydal.adapters.base.BaseAdapter method), 7
 - varquote() (pydal.adapters.mssql.MSSQLAdapter method), 21
 - varquote() (pydal.adapters.mysql.MySQLAdapter method), 23
 - varquote() (pydal.adapters.postgres.PostgreSQLAdapter method), 26
 - varquote_aux() (in module pydal.helpers.methods), 31

VerticaAdapter (class in pydal.adapters.mssql), 22
Virtual (pydal.objects.Field attribute), 42
VirtualCommand (class in pydal.objects), 47

W

warn_bad_usage() (pydal.helpers.classes.FakeCursor method), 29
web2py_extract() (pydal.adapters.sqlite.SQLiteAdapter static method), 27
web2py_filesystems (pydal.helpers.classes.DatabaseStoredFile attribute), 28
web2py_regexp() (pydal.adapters.sqlite.SQLiteAdapter static method), 27
with_alias() (pydal.base.DAL.Table method), 36
with_alias() (pydal.objects.Expression method), 42
with_alias() (pydal.objects.Table method), 47
write() (pydal.helpers.classes.DatabaseStoredFile method), 28

X

xml() (pydal.objects.BasicRows method), 40
xorify() (in module pydal.helpers.methods), 31

Y

year() (pydal.objects.Expression method), 42